

GS Series 630 User Manual Addendum

This document is an addendum to the GS Series 630 User manual.

The following topics in the GS Series 630 User manual contain updates:

- Optional accessories topic in the *GS Series 630-635 User manual (P/N: 020-001213-XX)*
- Adjusting the projector position topic in the *GS Series 630-635 User manual (P/N: 020-001213-XX)*

Adjusting the projector position

When you select a position for the projector, consider the size and shape of your screen, the location of your power outlets, and the distance between the projector and the rest of your equipment. Follow these general guidelines:

- Position the projector on a flat surface at a right angle to the screen. The projector (with the standard lens) must be at least 3 feet (0.9 m) from the projection screen.
- Position the projector to the required distance from the screen. The distance from the lens of the projector to the screen, the zoom setting, and the video format determine the size of the projected image.
- Determine the lens throw ratio:
 - Lens 0.65~0.75:1 (WU)
 - Lens 0.75~0.95 (WU)
 - Lens 0.95~1.22 (WU)
 - Lens 1.22~1.52 (WU)
 - Lens 1.52~2.9 (WU)
 - Lens 2.9~5.5 (WU)
- 360 degree free orientation operation

List of components

This projector comes with all the items listed below. Check to make sure your package is complete. If anything is missing, contact your dealer.

- IR remote control (P/N: 003-004468-01)
- Power cords supplied with the projector:
 - UK/Korea/Russia
 - North America

- Europe
- Australia/New Zealand
- Japan
- India
- South Africa

- DVI to HDMI dongle
- User manual (USB)

Due to the difference in applications for each country, some regions may have different accessories.

The following accessories are available for the projector:

- Cable Cover GS White (P/N: 140-106108-XX)
- Cable Cover GS Black (P/N: 140-106119-XX)
- Standard Lens 1.22 - 1.53 (P/N: 140-132107-XX)
- Optional Lens 0.65-0.75:1 (P/N: 140-143109-XX)
- Optional Lens 0.95 - 1.22 (P/N: 140-101103-01)
- Optional Lens 1.52 - 2.89 (P/N: 140-102104-01)
- Optional Lens 0.75 - 0.95 (P/N: 140-119102-XX)
- Optional Lens 2.90 - 5.50 (P/N: 140-107109-XX)
- Optional Lens 1.22-1.52 (P/N: 140-131106-XX)
- Optional Lens 0.36 (P/N: 140-133108-XX)
- Christie One Mount (P/N: 108-506102-XX)
- One Mount Extender Rod (P/N: 121-125109-XX)
- One Mount Rigging Kit (P/N: 121-126100-XX)

Technical support

Technical support for Christie Enterprise products is available at:

- North and South America: +1-800-221-8025 or Support.Americas@christiedigital.com
- Europe, Middle East, and Africa: +44 (0) 1189 778111 or Support.EMEA@christiedigital.com
- Asia Pacific (support.apac@christiedigital.com):
 - Australia: +61 (0)7 3624 4888 or tech-Australia@christiedigital.com
 - China: +86 10 6561 0240 or tech-supportChina@christiedigital.com
 - India: +91 (80) 6708 9999 or tech-India@christiedigital.com
 - Japan: 81-3-3599-7481
 - Singapore: +65 6877-8737 or tech-Singapore@christiedigital.com
 - South Korea: +82 2 702 1601 or tech-Korea@christiedigital.com
- Christie Professional Services: +1-800-550-3061 or NOC@christiedigital.com