

CHRISTIE®

Direct-view products

LCD digital signage

Christie Access II Series | Corporate | Education | Retail | Digital signage

Model(s)

- UHD552-L
- UHD652-L
- UHD752-L
- UHD862-L
- UHD982-P-A



Specifications

- Available sizes: 55", 65", 75", 86", 98"
- Native resolution: 4K UHD (3840 x 2160) (16:9)
- Brightness range: 350-500 nits
- Backlight: Direct-lit and edge-lit models
- LED lifespan: 50,000 hours to 50% brightness
- Run-time: 16/7 - 24/7 (983-P-A is 24/7) operation
- Display orientations: Landscape - 55", 65", 75", 86", Landscape and portrait - 98"
- Pixel pitch range: 0.315 x 0.315mm - 0.57 x 0.57mm
- Built-in speakers

We thought of everything

- Brilliant, large-format LCD displays
- 4K UHD
- OPS slot
- USB playback
- ADA-compliant
- Offers the highest brightness in the affordable display category

QR code



Christie Secure Series II | Government | Control rooms | Corporate | Digital signage

Model(s)

- SUHD553-L
- SUHD653-L
- SUHD753-L
- SUHD863-L
- SUHD983-PA



Specifications

- Available sizes: 55", 65", 75", 86", 98"
- Native resolution: 4K UHD (3840 x 2160) (16:9)
- Brightness range: 450-500 nits
- Backlight: Direct-lit and edge-lit models
- LED lifespan: 30,000 - 50,000 hours to 50% brightness
- Run-time: All models designed for 18/7 operation; SUHD983-P designed for 24/7 operation
- Display orientations: Landscape - 55", 65", 75", 86", Landscape and portrait - 98"
- Pixel pitch range: 0.315 x 0.315mm - 0.57 x 0.57mm
- Built-in speakers

We thought of everything

- Commercial-grade 4K UHD LCD panels specifically designed for secure-facility applications
- Non-RF for increased security
- TAA-compliant
- ADA-compliant
- Multiple connectivity options
- 4K multi-source viewing capability

QR code



CHRISTIE®

LCD video walls

Christie Extreme Series | Control rooms | Corporate | Education | Retail | Architecture and art galleries | Hospitality

Model(s)

- FHD554-XZ-H
- FHD554-XZ
- FHD554-XZ-HR
- FHD554-XZ-R



Specifications

- Size: 55"
- Bezel width: 0.88mm (0.44 per display)
- Native resolution: Full HD (1920 x 1080) (16:9)
- Brightness: 500-700 nits
- Backlight: Direct-lit
- LED lifespan: 60,000 hours to 50% brightness
- Run-time: 24/7 operation
- Display orientations: Landscape or portrait
- Pixel pitch: 0.63 x 0.63mm

We thought of everything

- Create near-seamless video walls with our Extreme-narrow bezel tiled LCD panels
- Featuring advanced panel matching and built-in video wall scaling
- Smart Light Control for uniformity and consistency
- Fast motion compensation to reduce tearing of video wall content
- 24/7 operation
- Remote and redundant power options
- ADA-compliant
- Select models are TAA-compliant

QR code



Christie Ultra Series | Critical viewing | Control rooms | Government | Corporate | Retail | Hospitality

Model(s)

- FHD554-X



Specifications

- Size: 55"
- Bezel width: 3.5mm combined
- Native resolutions: Full HD (1920 x 1080) and 4K UHD (3840 x 2160)
- Brightness range: 500 nits
- Backlight: Direct-lit
- LED lifespan: 50,000 hours to 50% brightness
- Run-time: 24/7 operation
- Display orientations: Landscape or portrait
- Pixel pitch: 0.63 x 0.63mm

We thought of everything

- Professional-grade, ultra-narrow bezel width for near-seamless LCD video walls
- Up to 4K UHD, built-in video processing, and 24/7 operation
- Advanced panel matching ensures image uniformity and fast installation
- Built-in video wall scaling supports 4K signals across video walls up to 10x10 configurations
- ADA-compliant
- Non-RF and TAA-compliant

QR code



LED video walls

Christie Core Series III | Public spaces | Corporate | Education | Government | Control rooms

Model(s)

- LED009-C3-I
- LED012-C3-I
- LED015-C3-I
- LED018-C3-I
- LED025-C3-I



Specifications

- Pixel pitches: 0.9mm, 1.2mm, 1.5mm, 1.8mm, 2.5mm
- Brightness: 800 nits (cd/m²)
- Pixel density range: 1,137,777 - 160,000 pixels/m²
- Aspect ratio: 16:9
- Contrast ratio: 5,000:1 @ 1Lux, 2,000:1 @ 10Lux
- Compatible with our E600 controller

We thought of everything

- Reliable, affordable, high-value LED video walls
- Lighter and more power efficient than previous models
- Simple, concealed cable design
- Redundant on-board power
- Full-front access for easy installation and service
- ADA-compliant direct-mount system
- Scales to common resolutions including HD and 4K
- Powered by our E600 controller for simple system design and enhanced processing that can deliver 4K at 60 Hz, HDR10, and low-brightness enhancements

QR code



LED video walls (continued)

Christie MicroTiles LED | Architectural | Broadcast | Corporate | Education | Museums | Government | Control rooms

Model(s)

- LED 0.75 P3
- LED 1.0 P3
- LED 1.5 P3
- LED 1.25 NTSC
- LED 1.5 NTSC



Specifications

- Pixel pitches: 0.75mm, 1.0mm, 1.25mm, 1.5mm
- Brightness: 1000-2000 nits (cd/m²)
- Contrast ratio: >5,000-1
- Refresh rate: Up to 3840 Hz
- Run time: 24/7
- Orientation: Landscape or portrait
- Color space: P3 and NTSC
- Display colors: 4.4 trillion (14-bit) / 208 trillion (16-bit)

We thought of everything

- Advanced, cabinet-free, ultra-lightweight MicroTiles® LED video wall technology
- Click-n-Go™ magnetic tiles eliminate alignment requirements and drastically increase installation speed
- Limitless design freedom—including 90° inside/outside corners and concave and convex curves
- Superior visual quality - Powerful processing along with HDR10 compatibility plus high-brightness and cinema-quality color for brilliant, true-to-life detail
- QuickMount™ system uses mounting sheets that help eliminate alignment challenges, and save time and money
- IR Neighbor Detection™ - Individual tiles automatically detect and self-locate
- AutoMatch™ automatically matches color and brightness for >97% uniformity across the entire display
- Increased reliability - The 0.75 and 1.0mm models are more reliable, easier to maintain, and have a longer life
- Increased durability - The surface of the 0.75 and 1.00mm models helps protect against dust and scratches, and offers the durability required to add interactive touch
- TAA-compliant

QR code



CHRISTIE[®]

christiedigital.com

For the most current specification information, please visit christiedigital.com

Copyright 2024 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP[®] and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.
CD4167-Direct-view-linecard-Jan-24-EN

