

Christie Vive Audio

CDA Series

CDA2 2000W class D amplifier



Technical Specifications		Christie CDA2
Rated power	bridge 4 ohms	• 1960W @ 1kHz 1% T.H.D.
	bridge 8 ohms	• 1160W @ 1kHz 1% T.H.D.
	2 x 2 ohms	• 980W per channel @ 1kHz 1% T.H.D. both channels driven
	2 x 4 ohms	• 540W per channel @ 1kHz at <0.1% T.H.D. both channels driven
	2 x 8 ohms	• 275W per channel @ 1kHz at <0.1% T.H.D. both channels driven
	1 x 2 ohms	• 1050W @ 1kHz at <0.1% T.H.D.
	1 x 4 ohms	• 600W @ 1kHz at <0.1% T.H.D.
	1 x 8 ohms	• 290W @ 1kHz at <0.1% T.H.D.
Minimum load impedance		• 2 ohms
Maximum RMS voltage swing		• 56V
Frequency response		• 10Hz-45kHz; 0dB, -3dB @ 1W
T.H.D.	2 x 2 ohms	• <0.1% @ 800W per channel from 20Hz-10kHz, decreasing to 760W @ 20kHz
	2 x 4 ohms	• <0.1% @ 500W per channel from 20Hz-20kHz
	2 x 8 ohms	• <0.1% @ 270W per channel from 20Hz-20kHz
Input CMRR		• >-77dB @ 1kHz
Voltage gain		• x60 (+35dB)
Crossover		• 100Hz switchable 2nd order high pass and 3rd order low pass per channel
Crosstalk		• >-70dB @ 1kHz at 100W power @ 4 ohms
Hum and noise		• >-100dB, "A" weighted referenced to rated power @ 4 ohms
Slew rate		• >12V/μs
Damping factor (8 ohms)		• >250:1 @ 20Hz-1kHz @ 8 ohms
Phase response		• +6 to -70° from 20Hz-20kHz
Input sensitivity		• 0.775V ±3% for 1kHz 4 ohm rated power • 0.735V ± 3% for 1kHz 2 ohm rated power
Input impedance		• 15k ohms balanced • 7.5k ohms unbalanced
Current draw	@ 1/8 power	• 620W @ 2 ohms • 390W @ 4 ohms • 250W @ 8 ohms
	@ 1/3 power	• 1250W @ 2 ohms • 810W @ 4 ohms • 460W @ 8 ohms
Cooling		• Temperature dependent variable speed 80mm DC fan
Controls		• 2 front panel attenuators • Crossover select switch for H.P.F, Normal and L.P.F • Input mode switch for Stereo, Bridge and Parallel
Indicator LEDs		• 2 DDT (ACL clip limiting) • 2 signal presence • 2 active status • 2 temp • 2 DC protect
Protection		• Thermal • DC • Subsonic • Incorrect loads • Under and over voltage
Connectors	inputs	• Neutrik Dual Combi 1/4" XLR
	outputs	• Three Neutrik Speakon connectors for two channels plus common bridge
Construction		• 18 ga. galvanized steel
Dimensions		• (LxWxH) 10.5 x 19 x 3.5" (266 x 482 x 89mm) behind front panel + 0.6" for handle • 2 RU mounting
Net weight		• 10.90lbs (4.94kg) ¹
Gross weight		• 13.3lbs (6.02kg)
Warranty		• Limited 3-year warranty

Rated power readings made with BW: <10Hz-22kHz. All power measurements made at 120 VAC. 2 ohm power is time limited by circuit breaker.
Input power requirements: 120 VAC, 60Hz, 5A.

¹ Net weight does not include power cord.

Corporate offices

Christie Digital Systems USA, Inc.
Cypress
ph: 714 236 8610

Christie Digital Systems Canada Inc.
Kitchener
ph: 519 744 8005

Worldwide offices

Australia
ph: +61 (0) 7 3624 4888

Brazil
ph: +55 (11) 2548 4753

China (Beijing)
ph: +86 10 6561 0240

China (Shanghai)
ph: +86 21 6278 7708

France
ph: +33 (0) 1 41 21 44 04

Germany
ph: +49 2161 664540

India
ph: +91 (080) 6708 9999

Japan (Tokyo)
ph: 81 3 3599 7481

Korea (Seoul)
ph: +82 2 702 1601

Mexico
ph: +52 55-4744-1790

Republic of South Africa
ph: +27 11 251 0000

Russian Federation
and Eastern Europe
ph: +36 (0) 1 47 48 100

Singapore
ph: +65 6877 8737

Spain
ph: +34 91 633 9990

United Arab Emirates
ph: +971 4 3206688

United Kingdom
ph: +44 (0) 118 977 8000

United States (Arizona)
ph: 602 943 5700

United States (New York)
ph: 646 779 2014

**Independent sales
consultant offices**

Italy
ph: +39 (0) 2 9902 1161



ISO 9001
ISO 14001
Kitchener Ontario

For the most current specification information, please visit www.christiedigital.com

Copyright 2016 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4248 Mar 16

CHRISTIE