

Christie Vive Audio

CDA Series

CDA5 5000W class D amplifier



Technical Specifications		Christie CDA5
Rated power	2 x 2 ohms	• 2500W per channel @ 1kHz 0.35% T.H.D. both channels driven
	2 x 4 ohms	• 1500W per channel @ 1kHz at <0.1% T.H.D. both channels driven
	2 x 8 ohms	• 850W per channel @ 1 kHz at <0.1% T.H.D. both channels driven
	1 x 2 ohms	• 2800W @ 1kHz at <0.1% T.H.D.
	1 x 4 ohms	• 1700W @ 1kHz at <0.1% T.H.D.
	1 x 8 ohms	• 925W @ 1kHz at <0.1% T.H.D.
Minimum load impedance		• 2 ohms
Maximum RMS voltage swing		• 105V
Frequency response		• 20Hz-30kHz; 0dB, -3dB @ 1W
T.H.D.	2 x 2 ohms	• <0.2% @ 2000W per channel from 20Hz-4kHz, decreasing to 1500W @ 20kHz
	2 x 4 ohms	• <0.1% @ 1400W per channel from 20Hz-20kHz
	2 x 8 ohms	• <0.1% @ 830W per channel from 20Hz-20kHz, increasing to 1000W @ 20kHz
Input CMRR		• >-75dB @ 1kHz
Voltage gain		• x40 (+32dB)
Crossover		• 100Hz switchable 2nd order high pass and 3rd order low pass per channel
Crosstalk		• >-60dB @ 1kHz at 700Ws power @ 8 ohms
Hum and noise		• >-105dB, "A" weighted referenced to rated power @ 8 ohms
Slew rate		• >12V/μs
Damping factor (8 ohms)		• >210:1 @ 20Hz-1kHz @ 8 ohms
Phase response		• +5 to -91° from 20Hz-20kHz
Input sensitivity		• 1.94V ±3% for 1kHz 4 ohm rated power • 1.79V ±3% for 1kHz 2 ohm rated power
Input impedance		• 20k ohms balanced • 10k ohms unbalanced
Current draw	@ 1/8 power	• 848W @ 2 ohms • 522W @ 4 ohms • 338W @ 8 ohms
	@ 1/3 power	• 2077W @ 2 ohms • 1200W @ 4 ohms • 696W @ 8 ohms
Cooling		• 3 temperature dependent variable speed fans
Controls		• 2 front panel attenuators • Crossover select switch for H.P.F, Normal and L.P.F.
Indicator LEDs		• 2 ACL (clip limiting) • 2 signal presence • 2 active status • 2 temp • 2 DC protect
Protection		• Thermal • DC • Subsonic • Incorrect loads • Under and over voltage
Connectors	inputs	• Neutrik Dual Combi 1/4" XLR
	outputs	• Dual 1/4" signal patch • Neutrik Speakon Dual 4-pin twist-lock connectors
Construction		• 0.062" thick aluminum
Dimensions		• (LxWxH) 17.5 x 19 x 3.5" (444 x 482 x 89mm) behind front panel + 0.75" for front panel
Net weight		• 14.2lbs (6.4kg) ¹
Gross weight		• 18lbs (8.2kg)
Warranty		• Limited 3-year warranty

Rated power readings made with BW: <10Hz-22kHz. All power measurements made at 120 VAC. 2 ohm power is time limited by circuit breaker.
Input power requirements: 120 VAC, 60Hz, 5A.

¹ Net weight does not include power cord.

United Kingdom
Branch & EMEA
Head Office
ViewPoint
200 Ashville Way
Wokingham
Berkshire, U.K.
RG41 2PL
PH: +44 (0) 118 977 8000

Middle East
Light Industrial Unit (LIU-17)
Nad Al Shibba
Sheikh Mohammed Bin Zayed Road
Dubai Silicon Oasis
PO Box: 293762
Dubai - U.A.E
PH: +971 (0) 4 503 6800

Africa
Unit C3
Northlands Deco Park
New Market Road
Northriding
Randburg
2164
Johannesburg
Gauteng
South Africa
PH: +27 71 335 8667

Other EMEA offices

Germany
Branch Office
PH: +49 2161 566 200

France
Branch Office
PH: +33 (0) 1 41 21 44 04

Eastern Europe
Representative Office
PH: +36 (0)1 47 48 138

Spain
Branch Office
PH: +34 91 633 9990

Italy
Independent Sales Consultant Office
PH: +39 (0) 2 9902 1161

Russia
Independent Sales Consultant Office
PH: +7 (495) 930-8961



For the most current specification information, please visit www.christieemea.com

Copyright 2016 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.
Printed in Canada on recycled paper. 4250 Mar 16

CHRISTIE[®]