

# Christie Vive Audio

## CDA Series

### CDA7.5 7500W class D amplifier



Technical Specifications		Christie CDA7.5
Rated power	2 x 2 ohms	• 3790W per channel @ 1kHz 1% T.H.D. both channels driven
	2 x 4 ohms	• 2030W per channel @ 1kHz at <0.1% T.H.D. both channels driven
	2 x 8 ohms	• 1170W per channel @ 1kHz at <0.1% T.H.D. both channels driven
	1 x 2 ohms	• 3900W @ 1kHz at <0.1% T.H.D.
	1 x 4 ohms	• 2400W @ 1kHz at <0.1% T.H.D.
	1 x 8 ohms	• 1300W @ 1kHz at <0.1% T.H.D.
Minimum load impedance		• 2 ohms
Maximum RMS voltage swing		• 124V
Frequency response		• 20Hz-30kHz; 0dB, -3dB @ 1W
T.H.D.	2 x 2 ohms	• <0.5% @ 3390W per channel from 20Hz-4kHz, decreasing to 3100W @ 20kHz
	2 x 4 ohms	• <0.1% @ 1850W per channel from 20Hz-20kHz
	2 x 8 ohms	• <0.1% @ 1170W per channel from 20Hz-10kHz, increasing to 1350W @ 20kHz
Input CMRR		• >-75dB @ 1kHz
Voltage gain		• x40 (+32dB)
Crossover		• 100Hz switchable 2nd order high pass and 3rd order low pass per channel
Crosstalk		• >-60dB @ 1kHz at 1000Ws power @ 8 ohms
Hum and noise		• >-100dB, "A" weighted referenced to rated power @ 4 ohms
Slew rate		• >12V/μs
Damping factor (8 ohms)		• >200:1 @ 20Hz-1kHz @ 8 ohms
Phase response		• +15 to -85° from 20Hz-20kHz
Input sensitivity		• 2.25V ±3% for 1kHz 4 ohm rated power • 2.20V ±3% for 1kHz 2 ohm rated power
Input impedance		• 20k ohms balanced • 10k ohms unbalanced
Current draw	@ 1/8 power	• 1348W @ 2 ohms • 757W @ 4 ohms • 504W @ 8 ohms
	@ 1/3 power	• 3185W @ 2 ohms • 1654W @ 4 ohms • 907W @ 8 ohms
Cooling		• 3 temperature dependent variable speed fans
Controls		• 2 front panel attenuators • Crossover select switch for High Out, Normal and Subwoofer
Indicator LEDs		• 2 ACL (clip limiting) • 2 signal presence • 2 active status • 2 temp • 2 DC protect
Protection		• Thermal • DC • Subsonic • Incorrect loads • Under and over voltage
Connectors	inputs	• Neutrik Dual Combi 1/4" XLR
	outputs	• Dual 1/4" signal patch • Neutrik Speakon Dual 4-pin twist-lock connectors
Construction		• 0.062" thick aluminum
Dimensions		• (LxWxH) 17.5 x 19 x 3.5" (444 x 482 x 89mm) behind front panel + 0.75" for front panel
Net weight		• 15.2lbs (6.9kg) <sup>1</sup>
Gross weight		• 19.0lbs (8.6kg)
Warranty		• Limited 3-year warranty

Rated power readings made with BW: <10Hz-22kHz. All power measurements made at 120 VAC. 2 ohm power is time limited by circuit breaker.  
Input power requirements: 120 VAC, 60Hz, 5A.

<sup>1</sup> Net weight does not include power cord.

**United Kingdom**  
Branch & EMEA  
Head Office  
ViewPoint  
200 Ashville Way  
Wokingham  
Berkshire, U.K.  
RG41 2PL  
PH: +44 (0) 118 977 8000

**Middle East**  
Light Industrial Unit (LIU-17)  
Nad Al Shibba  
Sheikh Mohammed Bin Zayed Road  
Dubai Silicon Oasis  
PO Box: 293762  
Dubai - U.A.E  
PH: +971 (0) 4 503 6800

**Africa**  
Unit C3  
Northlands Deco Park  
New Market Road  
Northriding  
Randburg  
2164  
Johannesburg  
Gauteng  
South Africa  
PH: +27 71 335 8667

#### Other EMEA offices

**Germany**  
Branch Office  
PH: +49 2161 566 200

**France**  
Branch Office  
PH: +33 (0) 1 41 21 44 04

**Eastern Europe**  
Representative Office  
PH: +36 (0)1 47 48 138

**Spain**  
Branch Office  
PH: +34 91 633 9990

**Italy**  
Independent Sales Consultant Office  
PH: +39 (0) 2 9902 1161

**Russia**  
Independent Sales Consultant Office  
PH: +7 (495) 930-8961



For the most current specification information, please visit [www.christieemea.com](http://www.christieemea.com)



Copyright 2016 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.  
Printed in Canada on recycled paper. 4251 Mar 16

**CHRISTIE®**