

# Christie Vive Audio

## LS Series

### LS2S line source surround loudspeaker




Specifications	Christie LS2S
<b>System type</b>	• Two-way, passive, ported enclosure
<b>Driver components</b>	• HF: 3" high output ribbon driver with Kapton® diaphragm and Neodymium magnets • LF: 8" paper/Kevlar composite cone driver with 51mm diameter voice coil
<b>Crossover</b>	• 2-way, passive @ 2.2kHz
<b>Frequency response<sup>1</sup></b>	• 70Hz-20kHz @ -6dB
<b>Maximum SPL<sup>2</sup></b>	• 116.5dB continuous, 128dB peak
<b>System coverage<sup>3</sup></b>	• 100° horizontal dispersion • 50° vertical dispersion
<b>Sensitivity<sup>1</sup>, 1W/1m</b>	• 94dB
<b>Power handling capacity<sup>2</sup></b>	• 175W continuous, 300W (IEC) short term
<b>Recommended amplifier power</b>	• 200-300W @ 8 ohms
<b>Rated impedance</b>	• 8 ohms
<b>Input connectors</b>	• Screw terminal barrier strip
<b>Enclosure</b>	• Polymer composite enclosure with extensive structural reinforcements • Ported enclosure • Acoustically transparent fabric grille
<b>Mounting options</b>	• Wall mounted using 4 x M6 points on rear
<b>Accessories</b>	• 145-179108-01: BKTW-LSXS - Wall tilt bracket for LSxS surround loudspeakers (optional) • 145-108100-XX Christie S115 subwoofer (for optional bass management) • 145-103105-XX Christie S215 subwoofer (for optional bass management) • 111-694201-XX: Allen Products MM-017 for wall mounting (optional)
<b>Dimensions</b>	• (LxWxH) 9.6 x 10.24 x 17.7" (244 x 260 x 450mm)
<b>Net weight</b>	• 15.4lbs (7kg)
<b>Warranty</b>	• Limited 5-year warranty

<sup>1</sup> Measured at 2m on tweeter axis in simulated free field conditions. Near field measurements were used for low-frequency data. Sensitivity is calculated based on measured SPL response averaged in 200Hz-5kHz range.


<sup>2</sup> IEC refers to IEC 60268-5 standard. Max SPL calculated based on sensitivity and power handling. IEC short-term power tested using IEC pink noise with 9dB crest factor. The crest factor was specifically increased to reflect real-life parameters of digital cinema sound tracks. Maximum peak SPL calculated using peak voltage during IEC short-term power test. Continuous power handling tested using IEC60268-1 noise signal for duration of 2 hours.

<sup>3</sup> Averaged in 500Hz-12kHz range, at -6dB.


Top view



Side view



Front view



#### Corporate offices

Christie Digital Systems USA, Inc.  
Cypress  
ph: 714 236 8610

Christie Digital Systems Canada Inc.  
Kitchener  
ph: 519 744 8005

#### Worldwide offices

Australia  
ph: +61 (0) 7 3624 4888

Brazil  
ph: +55 (11) 2548 4753

China (Beijing)  
ph: +86 10 6561 0240

China (Shanghai)  
ph: +86 21 6278 7708

France  
ph: +33 (0) 1 41 21 44 04

Germany  
ph: +49 2161 664540

India  
ph: +91 (080) 6708 9999

Japan (Tokyo)  
ph: 81 3 3599 7481

Korea (Seoul)  
ph: +82 2 702 1601

Mexico  
ph: +52 55-4744-1790

Republic of South Africa  
ph: +27 11 251 0000

Russian Federation and Eastern Europe  
ph: +36 (0) 1 47 48 100

Singapore  
ph: +65 6877 8737

Spain  
ph: +34 91 633 9990

United Arab Emirates  
ph: +971 4 3206688

United Kingdom  
ph: +44 (0) 118 977 8000

United States (Arizona)  
ph: 602 943 5700

United States (New York)  
ph: 646 779 2014

#### Independent sales consultant offices

Italy  
ph: +39 (0) 2 9902 1161



For the most current specification information, please visit [www.christiedigital.com](http://www.christiedigital.com)

Copyright 2016 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4220 Mar 16

# CHRISTIE®