

# S Series

Powerful, accurate, versatile subwoofers

Digital cinema | Post production | Premium large format

The Christie® Vive Audio™ S Series of cinema subwoofers employ premium grade components and an advanced cabinet design with Extended Bass Shelf (EBS) tuning for powerful and accurate low frequency audio reproduction. Each ported, high cubic displacement cabinet is heavily cross-braced and features 15" or 18" drivers with long linear excursions and dual 4" voice coils.



**CHRISTIE®**  
VIVE AUDIO

# Powerful, accurate, versatile subwoofers

Christie® Vive Audio™ S Series subwoofers offer low distortion, low power compression and minimal turbulence to deliver extended low frequency response at extremely high output levels for powerful and deep bass.

The S118LP and S218LP models are engineered for the reproduction of Low Frequency Effects (LFE). The S115 and S215 models can be combined with our LA Series loudspeakers to create full-range audio systems that can be used as screen channels or as corner surrounds for bass management. Integrated fly points offer installation flexibility.



## Special features

- › High cubic displacement cabinet, heavily cross-braced, ported and tuned
- › Each driver has a discrete, internal ported enclosure for optimal performance
- › Extra-large port area with rounded edges for minimal air turbulence noise
- › S115 and S215 models are overhead rated for safe installs utilizing integrated fly points
- › Backed by a limited 5-year warranty



## S Series product line



**S115**

**S215**

**S118LP**

**S218LP**

	<b>S115</b>	<b>S215</b>	<b>S118LP</b>	<b>S218LP</b>
<b>Application</b>	Bass management	Bass management	Low frequency effects	Low frequency effects
<b>System type</b>	Subwoofer, ported enclosure, with EBS tuning			
<b>Driver components</b>	1 x 15" low frequency driver with dual 4" voice coils and long linear excursion	2 x 15" low frequency drivers each with dual 4" voice coils and long linear excursion	1 x 18" low frequency driver with dual 4" voice coils and long linear excursion	2 x 18" low frequency drivers each with dual 4" voice coils and long linear excursion
<b>Frequency response</b>	27-300Hz @ -10dB 30-250Hz @ -6dB	27-300Hz @ -10dB 30-250Hz @ -6dB	20-250Hz @ -10dB 24-200Hz @ -6dB	20-250Hz @ -10dB 24-200Hz @ -6dB
<b>Maximum SPL</b>	125dB SPL continuous, 137dB SPL peak	131dB SPL continuous, 143dB SPL peak	127.5dB SPL continuous, 139.5dB SPL peak	133.5dB SPL continuous, 145.5dB SPL peak
<b>Sensitivity</b>	1W/1m: 97dB (40-150Hz)	1W/1m: 100dB (40-150Hz)	1W/1m: 97.5dB (40-150Hz)	1W/1m: 100.5dB (40-150Hz)
<b>Power handling</b>	600W (AES) continuous 1200W (IEC) short term	1200W (AES) continuous 2400W (IEC) short term	1000W (AES) continuous 2000W (IEC) short term	2000W (AES) continuous 4000W (IEC) short term
<b>Rated impedance</b>	8 ohms	4 ohms	8 ohms	4 ohms

#### Corporate offices

---

Christie Digital Systems USA, Inc.  
Cypress  
ph: 714 236 8610

Christie Digital Systems Canada Inc.  
Kitchener  
ph: 519 744 8005

#### Independent sales consultant offices

---

Italy  
ph: +39 (0) 2 9902 1161

Russia  
ph: +7 (495) 930 8961

#### Worldwide offices

---

Australia  
ph: +61 (0) 7 3624 4888

Brazil  
ph: +55 (11) 2548 4753

China (Beijing)  
ph: +86 10 6561 0240

China (Shanghai)  
ph: +86 21 6030 0500

Columbia  
ph: +57 (318) 447 3179

Eastern Europe  
ph: +36 (0) 1 47 48 138

France  
ph: +33 (0) 1 41 21 44 04

Germany (Cologne)  
ph: +49 221 99 512-0

Germany (Moechengladbach)  
ph: +49 2161 566200

India  
ph: +91 (080) 6708 9999

Japan  
ph: +81 3 3599 7481

Mexico  
ph: +52 55 4744 1790

Republic of South Africa  
ph: +27 11 251 0000

Singapore  
ph: +65 6877 8737

South Korea  
ph: +82 2 702 1601

Spain  
ph: +34 91 633 9990

United Arab Emirates  
ph: +971 (0) 4 503 6800

United Kingdom  
ph: +44 (0) 118 977 8000

United States (Arizona)  
ph: 602 943 5700

United States (New York)  
ph: 646 779 2014



For the most current specification information, please visit [www.christiedigital.com](http://www.christiedigital.com)

Copyright 2018 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.  
Printed in Canada on recycled paper. 4672 Mar 18

**CHRISTIE®**