

# Christie Velvet - Apex Series

## 0.9mm indoor LED tiles - landscape


Technical specifications		Christie LED009-AL
Display technology	pixel pitch	• 0.96mm
	pixel configuration	• 3-in-1 (1R1G1B)
	pixel density	• 1,083,681 pixels/m <sup>2</sup>
	maximum calibrated brightness	• 800 nits (cd/m <sup>2</sup> )
	aspect ratio	• 16:9
	contrast ratio (full field)	• 5000:1
	viewing angle	• 160° H, 140° V
	refresh rate	• ≥3200Hz
	scan rate	• 1/30
	color temperature	• 2700-9600K
Signal	display colors	• 4.39 trillion (14-bit)
	inputs	• HDMI (HDCP) • DVI (HDCP) • HDSOI
Power	input rating - remote power supply <sup>1</sup>	• 100-240 VAC @ 50-60Hz
	power consumption per cabinet	• 75W typical • 223W maximum
	heat output	• 256 BTU/hr typical • 761 BTU/hr maximum
Environment	operating temperature	• 32-104°F (0-40°C)
	operating humidity	• 10-90% non-condensing
	storage temperature	• 14-122°F (-10-55°C)
	environment	• Indoor
	IP rating	• 30
	LED lifespan (50% brightness)	• 100,000 hrs
	runtime	• 24/7
Physical	tile dimensions	• (WxHxD): 24.19 x 13.61 x 3.71" (614.4 x 345.6 x 94.3mm)
	tile area	• 2.29 ft <sup>2</sup> (0.2123m <sup>2</sup> )
	tile resolution	• 640 x 360 pixels
	tile weight	• 18.3lbs (8.3kg)
	tile array size to achieve 1920 x 1080	• 3 x 3
	cabinet design	• Die-cast aluminum
	orientation	• Landscape
	service access	• All service from front
	module dimensions	• (WxH): 6.05 x 4.54" (153.6 x 115.2mm)
	module resolution	• 160 x 120 pixels
	installation options	• Flat • Concave
additional required components	• Remote power supply, and controller sold separately	
Certifications - current and pending <sup>2</sup>	• CE (Includes EMC), FCC, CSA (UL60950), RCM, IRAM-S, CCC, EAC, UKR, KC	
Warranty	<ul style="list-style-type: none"> <li>• Three year parts and labor limited warranty</li> <li>• Contact an authorized Christie representative for full details</li> <li>• Extended warranty option available for a one-time fee at time of purchase</li> </ul>	

<sup>1</sup>See remote power supply specifications for full details.


<sup>2</sup>Certain of the listed certifications may be pending and not yet issued. For the current status of the listed certifications, please contact an authorized Christie representative.

Performance specifications are typical. Due to constant research, specifications are subject to change without notice.


### Front view



### Back view



### Side view



### Corporate offices

Christie Digital Systems USA, Inc.  
Cypress  
ph: 714 236 8610

Christie Digital Systems Canada Inc.  
Kitchener  
ph: 519 744 8005

### Worldwide offices

Australia  
ph: +61 (0) 7 3624 4888

Brazil  
ph: +55 (11) 2548 4753

China (Beijing)  
ph: +86 10 6561 0240

China (Shanghai)  
ph: +86 21 6278 7708

Columbia  
ph: +57 (318) 447 3179

Eastern Europe  
ph: +36 (0) 1 47 48 138

France  
ph: +33 (0) 1 41 21 44 04

Germany (Cologne)  
ph: +49 221 99 512-0

Germany (Moechengladbach)  
ph: +49 2161 566200

India  
ph: +91 (080) 6708 9999

Japan  
ph: +81 3 3599 7481

Mexico  
ph: +52 55 4744 1790

Republic of South Africa  
ph: +27 11 251 0000

Singapore  
ph: +65 6877 8737

South Korea  
ph: +82 2 702 1601

Spain  
ph: +34 91 633 9990

United Arab Emirates  
ph: +971 (0) 4 503 6800

United Kingdom  
ph: +44 (0) 118 977 8000

United States (Arizona)  
ph: 602 943 5700

United States (New York)  
ph: 646 779 2014

### Independent sales consultant offices

Italy  
ph: +39 (0) 2 9902 1161

Russia  
ph: +7 (495) 930 8961

For the most current specification information, please visit [www.christiedigital.com](http://www.christiedigital.com)

Copyright 2017 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4600 Dec 17

**CHRISTIE**