






REVISION HISTORY OF: 020-001243-01			
REV	DESCRIPTION OF CHANGE	BY	REV DATE
01	INITIAL RELEASE	RF	04/17/2017



LCD PANEL UHD651-L
135-018100-XX
(WITHOUT TOUCH OVERLAY)




DO NOT OBSTRUCT
AIRFLOW
(ALL INSTANCES)



DO NOT OBSTRUCT
AIRFLOW
(ALL INSTANCES)

- GENERAL NOTES:
- MASS: 24.7 ± 0.5 kg (54.3 ± 1.1 lbs)
 - OPERATING TEMPERATURE: 0 - 40°C (32 - 104°F) MAX.
 - MAX. POWER REQUIREMENTS: 140W (NOT INCLUDING OPS)
 - TYPICAL POWER CONSUMPTION: 73.0W (NOT INCLUDING OPS)
 - STANDBY POWER CONSUMPTION: ≤ 0.5W (NOT INCLUDING OPS)
 - TO ENSURE THE MOUNTING BRKT CLEARS ANY PROTRUSION ON THE REAR OF THE PANEL, CHRISTIE RECOMMENDS USING SPACERS WITH A MINIMUM HEIGHT OF 6.35MM (.25IN)

UNITS	INCHES	MILLIMETRES	DRAWN BY	E. FARBER	CHRISTIE DIGITAL SYSTEMS USA, INC. CHRISTIE DIGITAL SYSTEMS CANADA, INC.
UNLESS OTHERWISE SPECIFIED INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994			DRAWN DATE	06/17/2017	PART DESCRIPTION DWG LINE UHD651-L
TOLERANCES APPLY AS SHOWN BELOW			APPROVED BY	L. MCGILL	
DECIMAL PLACES	INCHES	MILLIMETRES	APPROVAL DATE	06/19/2017	PART NUMBER 020-001243-01
XXX	± .013	± 1.4	PROPRIETARY NOT TO BE DISCLOSED OR REPRODUCED IN ANY MANNER WITHOUT THE EXPRESS WRITTEN PERMISSION OF CHRISTIE		
XX	± .010	± 1.0	THIRD ANGLE PROJECTION		SHEET 1 OF 2
X	± .005	± 0.3	SCALE		
ANGULAR DIMENSIONS	° 10.0'		SCALE		1:5
XX°	° 0.5'		MASS		- LBS (- KG)
XX'X"	° 0.1'		SHEET 1 OF 2		



LCD PANEL UHD651-L
(135-018100-XX)
WITH TOUCH OVERLAY INSTALLED

