






REVISION HISTORY OF: 020-102867-01			
REV	DESCRIPTION OF CHANGE	BY	REV DATE
01	INITIAL RELEASE	TM	05/08/2018
02	CORRECTED POWER REQUIREMENTS NOTE	CE	07/10/2018



LENS TABLE (DIMENSIONS MM[IN])			
LENS	DIMENSION 'A'	DIMENSION 'B'	DIMENSION 'C'
1.05:1 Lens	203.2[8.00]	274.95[10.82]	1286.45[50.65]
1.2-1.75 Zoom Lens	141.2[5.56]	212.95[8.38]	1224.45[48.21]
1.39-1.9 Zoom Lens	171.3[6.74]	243.05[9.57]	1254.55[49.39]
1.5-2.2 Zoom Lens	172.2[6.78]	243.95[9.60]	1255.45[49.39]
1.75-2.4 Zoom Lens	93.6[3.69]	165.35[6.51]	1176.85[46.33]
1.9-3.0 Zoom Lens	88.2[3.47]	159.95[6.29]	1171.45[46.12]
2.4-3.9 Zoom Lens	79.40[3.13]	151.15[5.95]	1162.65[45.77]




**GENERAL NOTES:**

1. AMBIENT AIR TEMPERATURE: 10°C (50°F) TO 35°C (95°F) MAX.
2. MASS: 80 kg (176 lbs), NO LENS
3. TILT ANGLE:  
PITCH: +5°/-15°  
ROLL: +/- 3° EACH DIRECTION
4. POWER REQUIREMENTS:  
MAIN: SINGLE PHASE 200-240VAC, 50/60Hz, 18A  
UPC: 100-240VAC, 50/60Hz, 10A
5. POWER CONSUMPTION: 2800W
6. ROOM HEAT LOAD: 5118 BTU/HR
7. ALTITUDE 0-3000m (10,000FT)


UNITS	INCHES	MILLIMETRES	DRAWN BY	C. HANSON	CHRISTIE DIGITAL SYSTEMS USA, INC. CHRISTIE DIGITAL SYSTEMS CANADA, INC.
UNLESS OTHERWISE SPECIFIED INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994			DATE	11/14/2017	
TOLERANCES APPLY AS SHOWN BELOW			APPROVED BY	F. VANDEK	
APPROVAL DATE			DATE	07/11/2018	
DECIMAL PLACES			PROPRIETARY NOT TO BE DISCLOSED OR REPRODUCED IN ANY MANNER WITHOUT THE EXPRESS WRITTEN PERMISSION OF CHRISTIE		
XXX			± 0.03		
XX			± 0.13		
X			± 0.25		
ANGULAR DIMENSIONS			THIRD ANGLE PROJECTION		
XX°			± 1.0°		
XX.X°			± 0.5°		
PART DESCRIPTION			DWG LINE CP2320 RGB		
SIZE			E		
SCALE			1:5		
MASS			- LBS [ KG ]		
SHEET 1 OF 2			020-102867-01 02		



ACCESSORIES




DETAIL LOCKING FEET REAR  
TYP. 2X  
SCALE 1:1.5





DETAIL LOCKING FEET FRONT  
TYP. 2X  
SCALE 1:1.5

BRKT LOCKING REAR FOOT  
PART#: 011-104195-01  
(PART OF 108-416102-XX)

BRKT LOCKING FRONT FOOT  
PART#: 011-104203-01  
(PART OF 108-416102-XX)




SERIES II RACK STAND  
108-416102-XX



CASTERS MUST BE REMOVED  
TO ACHIEVE LISTED MINIMUM HEIGHT

MINIMUM CLEARANCE  
FOR AIRFLOW



1073.6 [ 42.3 ]

1031.6 [ 40.62" ] MIN. (WITHOUT CASTERS)  
1080.1 [ 42.52" ] MIN. (WITH CASTERS)  
1307.6 [ 51.48" ] MAX.