
Software Release Notes

HS Series 2K version 1.1.0

This document describes the changes from HS Series 2K version 1.0.0 to version 1.1.0.

Affected products

The following products are affected:

- DWU15-HS
- DWU15A-HS
- DWU19-HS
- DWU19A-HS
- DWU23-HS
- DWU23A-HS

Purpose of release

The primary purpose of this software release is:

- Added a Twist link and ambient temperature status on dashboard page.
- Added a Not Supported message for key size, layout, and swap when not in PIP/PBP mode.
- Added support for the Crestron V2 function in the web user interface.
- Fixed an error in Light Source mode in the web user interface when 3D mode is Frame Packing.
- Fixed translations in the user interface.
- Fixed an issue when saving warps from AP.
- Fixed an issue with the RS232 echo command.
- Fixed an issue where the lens calibration could not be performed under Pin Protect mode.
- Fixed an issue where the Status LED is white (white LED flashing) and no longer controls the projector at 110 V.

Technical support

Technical support for Christie Enterprise products is available at:

- North and South America: +1-800-221-8025 or Support.Americas@christiedigital.com
- Europe, Middle East, and Africa: +44 (0) 1189 778111 or Support.EMEA@christiedigital.com
- Asia Pacific (support.apac@christiedigital.com):
 - Australia: +61 (0)7 3624 4888 or tech-Australia@christiedigital.com
 - China: +86 10 6561 0240 or tech-supportChina@christiedigital.com
 - India: +91 (80) 6708 9999 or tech-India@christiedigital.com

- Japan: 81-3-3599-7481
- Singapore: +65 6877-8737 or *tech-Singapore@christiedigital.com*
- South Korea: +82 2 702 1601 or *tech-Korea@christiedigital.com*
- Christie Professional Services: +1-800-550-3061 or *NOC@christiedigital.com*