
Software Release Notes

MicroTiles LED firmware version 1.5.0

This document provides information on the MicroTiles LED 1.5.0 release.

Christie MicroTiles LED tiles are modular, high-quality image display units that can be configured to create small display configurations as well as larger more complex display canvases of virtually any size and shape.

Each tile captures a portion of the image and applies scaling, as required, which results in a single picture. The LED wall controller acts as the main system controller and coordinates with all connected tiles to form a canvas.

Christie MicroTiles LED tiles are designed to occupy a smaller more manageable install footprint with minimal mechanical and electronics components. The simplicity of the design ensures higher reliability and improved thermal management.

Christie recommends clearing the browser cache after performing a firmware upgrade and before operating the wall with the new software.

When upgrading from an earlier version to 1.4.0 or later, Christie recommends allowing five minutes after the reboot for the system to complete re-initialization of all LED modules before operating the wall with the new software.

All devices in the array must be on the same firmware version.

New features and changes

Added new module support in this release:

- Added support for 0.75 mm low brightness modules.

Accessing the MicroTiles LED web user interface

Learn how to access the web user interface.

The MicroTiles LED web user interface is supported on the following browsers:

- Google Chrome™
- Microsoft® Edge®
- Safari®

Access the web user interface to configure the array and monitor the status of the components.

1. In a web browser, enter the IP address of the LED wall controller.
The IP address is displayed on the LED wall controller display.
In configurations with two LED wall controllers, entering the IP address for either wall controller accesses the same web user interface settings.
2. Log into the session with the username and the password.
The username and password are case-sensitive.
3. Select **Login**.

Updating the MicroTiles LED software

To install available software updates use the MicroTiles LED web user interface.



Notice. If not avoided, the following could result in property damage.

- Do not disconnect the power source for any components during the update.



For normal operation, all devices in the array must have the same version of firmware.

1. Download the latest software from www.christiedigital.com and save it to the computer to be connected to the array for the update.
2. Log into the MicroTiles LED web user interface.
3. Select **System Settings**.
4. In the Software section, select **Upgrade**.
5. Navigate to the file saved in step 1 and select **OK**.
The update starts immediately and progresses in this order:
 - a. The LED wall controllers and Octrollers are updated.
 - b. After the Octrollers finish updating, the tiles are updated.When the update is finished, the status is displayed.
6. For the update to be applied, restart the array by selecting **Reboot**.
Christie recommends clearing the browser cache after performing a firmware upgrade and before running the new software on the array.

Technical support

Technical support for Christie Enterprise products is available at:

- North and South America: +1-800-221-8025 or Support.Americas@christiedigital.com
- Europe, Middle East, and Africa: +44 (0) 1189 778111 or Support.EMEA@christiedigital.com
- Asia Pacific (support.apac@christiedigital.com):
 - China: +86 10 6561 0240 or tech-supportChina@christiedigital.com
 - India: +91 (80) 6708 9999 or tech-India@christiedigital.com
 - Japan: 81-3-3599-7481
 - Singapore: +65 6877-8737 or tech-Singapore@christiedigital.com
 - South Korea: +82 2 702 1601 or tech-Korea@christiedigital.com