


# FRAME-EVO-C40H / C40H-US

## Mounting frame for projectors



Manual Version 1.1

Date	Revision No.	Author	Checked	Approved	Description
31.10.2024	1.0	TSN	GJN	VIU	First version
18.02.2026	1.1	TSN	VIU	TSN	Update on accessories

The following projectors can be mounted in this frame:

Christie Griffyn Serie
Griffyn 4K35-RGB
Griffyn 4K50-RGB



Note: The above table lists some projector models that are compatible. Please contact us if you are missing a projector.



Note: This manual is subject to change without further notice. The latest manual version can be found online at [www.exactsolutions.de](http://www.exactsolutions.de) or by contacting us directly.

### Contact

Tel.: +49 2204 9485 30

E-Mail: [info@exactsolutions.de](mailto:info@exactsolutions.de)

Web: [www.exactsolutions.de](http://www.exactsolutions.de)

## Table of content

<b>1. Preamble</b> .....	<b>2</b>
1.1 Tools required.....	2
<b>2. Safety instructions</b> .....	<b>3</b>
2.1 Warnings.....	3
2.2 Caution.....	8
2.3 Risk Situations.....	9
<b>3. Scope of delivery</b> .....	<b>11</b>
<b>4. Overview of model numbers</b> .....	<b>12</b>
4.1 FRAME-EVO-C40H / C40H-US designation.....	12
<b>5. Optional Accessories</b> .....	<b>12</b>
<b>6. Description of the product</b> .....	<b>14</b>
6.1 Intended use.....	14
6.2 Specifications.....	14
<b>7. Installing the projectors into the frame</b> .....	<b>15</b>
<b>8. Adjustment options</b> .....	<b>17</b>
<b>9. Stacking frames</b> .....	<b>19</b>
<b>10. Mounting the frame on a truss</b> .....	<b>20</b>
<b>11. Maximum stacking information</b> .....	<b>23</b>
<b>12. System maintenance and inspection (Re-examination)</b> .....	<b>27</b>
12.1 Mounting threads at bottom side.....	27
12.2 Sealed nuts with red coloured wax and other screw connections.....	28
12.3 Stacking points and locking pins.....	30
12.4 Screws and safety washers securing the projector in the frame.....	32
<b>13. Disposal of components</b> .....	<b>33</b>
13.1 Metal parts and packaging.....	33
13.2 Disposal of entire devices.....	33

**14. Declaration of Conformity .....34**  
**Imprint.....35**

## 1. Preamble

The FRAME-EVO-C40H has been developed and manufactured with the highest care and attention. However, improper handling can cause a risk for safety and / or damage. Read these instructions carefully before handling and installing the product so that you can safely enjoy your device. In the following pages, you will find all the needed information for a safe and fast installation.

After the installation is done properly, you can enjoy all the features of your new product. Please consider keeping the original box and packaging materials, in case you ever need to ship the frame.

**Model number: FRAME-EVO-C40H / C40H-US**

Copyright © 2026 EXACT solutions GmbH. All rights reserved.

### 1.1 Tools required

Tool required is a 8 mm hex key to mount the projector into the FRAME-EVO-C40H / C40H-US as well as a universal torque key.



Figure 1 Hex key 8 mm (Allen key)



Figure 2 Universal torque key

## 2. Safety instructions



These installation instructions must always be handed over to the person who is carrying out the installation.

Read these instructions carefully before installing the system.

### 2.1 Warnings



The FRAME-EVO-C40H / C40H-US frame is intended for use by fully qualified, trained and competent persons to provide safe and secure transportation, installation and adjustment of projectors.



Warning: Handling only by instructed, qualified and authorised person with a minimum age 18 years and of sound mind.



For indoor usage only

Only use the frame with projector in a closed environment (conference rooms, theatres, convention halls, etc.) where there is no wind, moisture, excessive heat etc.



Make sure that only the designated projectors are installed in this frame! Do not try to use it with other projectors because serious accidents can occur!



Always use a set of two riggings slings with steel cable insert and two shackles that are stable enough for the load including dynamic forces when falling into the rigging sling! (two sets of rigging sling and shackle are mandatory) Otherwise it is not allowed to use the product and serious accidents or death can happen.



When using EVO-LINK-SK or other solutions to act as a secondary safety device make sure that the load will not fall more than 10cm to avoid dynamic forces.

Depending on the installation, additional material like shackles might be necessary.



Do not remove or replace any parts of the projector frame on your own. Contact the manufacturer or service partner in case of damage or loss. Removing or replacing parts by non-certified companies or people might result in serious accidents and death.

## **Definition of qualified persons:**

### Trained/Qualified person

A person can be considered as trained/qualified when it has been thoroughly informed and/or trained about the assigned task and the possible dangers that can occur in case of improper behaviour and / or not observing precisely the installation instructions.

### Qualified/Specialised person

A person can be considered qualified or specialised when, based on specialised training, knowledge and experience, it can assess the work assigned and recognise possible dangers.

## **Only use the frame and its components for its intended use.**

- If this product is used for something else than its intended use, serious accidents and death may result. See chapter Intended use

## **Installation work should only be carried out by a qualified technician.**

- If this product is not installed correctly, serious accidents and death may result.

## **Do not use the FRAME-EVO-C40H / C40H-US frame outdoors.**

- This product is made only for indoor usage. If the FRAME-EVO-C40H / C40H-US frame is mounted outdoor, there are many influences like wind or rain that can have an effect on the stability of the whole system.
- This can cause property damage, serious accidents and death.

## **A visual inspection must be done prior to every installation, in which the system is involved. The inspection must be performed by a qualified person.**

- All parts of the frame must be inspected in detail prior to any usage
- Only if the frame and all its components are in a flawless condition, it is safe to use the system.
- For further details, see chapter 12. System maintenance and inspection (Re-examination)
- Using a projector frame which has damages, missing parts or the like can cause serious accidents and death.

**Only use projectors that are specified by the manufacturer to be used with the frame.  
When mounting the projector into the frame, use all screws and washers that are specified**

# Manual FRAME-EVO-C40H / C40H-US

---

**by the manufacturer. Make sure to tighten the screws safely, with the provided torque information**

- It is mandatory to use all screws and safety washers that the manufacturer defines to mount the projector. Use only the ones that are clearly specified.
- For a safe installation the screws must be tightened with the provided torque
- Using the wrong screws or washers is highly dangerous. Tightening the screw with a too low torque can cause the screw to loosen itself. Tightening the screw with a too high torque might cause structural damage to the screw or the thread inside the projector. Not using the safety washers enables the screw to loosen itself.
- Ignoring these instructions can cause the parts or the whole system to fall down and with this can cause death, serious injuries or product damage.

**Do not install the FRAME-EVO-C40H / C40H-US or the projector while people are present under the mounting zone during the installation process.**

- When installing the projector, make sure no one is in the area underneath the installation zone. Otherwise, this will be a risk for all people underneath, that could cause serious injuries and death.

**Do not place the frame on top of unstable surfaces.**

- If the frame or multiple frames are placed on the top of a surface, which is sloped or unstable, it /they may fall down or tip over and injury or damage could result. Make sure that the surface can support the overall weight of the frames including projectors and lens plus the weight of all additional equipment as well as other potential systems. The weight of one system consisting of projector, lens and EVO-FRAME is approx. 145 kg (320 lbs)<sup>1</sup>. A stack of up to three systems will result in a weight of approx. 435 kg (960 lbs)
- Using the product on unstable surfaces can cause serious accidents and death

**Make sure that the structure from which you hang up to two FRAME-EVO-C40H / C40H-US frames including projectors is capable of carrying the overall weight of approx. 290 kg (640 lbs) plus the weight of all additional equipment as well as other potential systems. Do not hang the frame from unstable or inappropriate structures.**

- Prior to any installation, you must do a visual inspection to make sure that the system is in a good condition. For more information, please refer to chapter “12. System maintenance and inspection (Re-examination)”

---

<sup>1</sup> Projector weight approx. 100 kg, heaviest lens approx. 10 kg, EVO-FRAME C40H 35 kg

# Manual FRAME-EVO-C40H / C40H-US

---

- If the frame is hung on an unstable structure, the entire system can fall down and injuries may occur. Make sure that the construction can support a total weight of up to 290 kg (640 lbs) plus the weight of all additional equipment as well as other potential systems. The above-named weight of 290 kg (640 lbs) represents the weight of two systems (projector, lens, EVO-FRAME-C40H). The weight of one system consisting of projector, lens and EVO-FRAME-C40H is approx. 145 kg (320 lbs)<sup>1</sup>.
- Ignoring this might cause significant damage to the product and serious accidents or death may result

## **Make sure to use only approved and recommended accessories to mount (hanging, standing) the EVO-FRAMEs**

- Do not use other accessories than the ones recommended and approved. Otherwise, using insufficient accessories may lead to serious injuries, death and property damage
- Please also refer to chapter "5. Optional Accessories"

## **Make sure to not exceed max. weight loads for ceiling mounting.**

- For suspended installations, use only designated hanging accessories. Please refer to the corresponding instructions for the accessories used. Do not overload these accessories and make sure the overall weight is within working specifications of the accessories. Please also refer to chapter "5. Optional Accessories" and "11. Maximum stacking information".
- Overloading the accessories and other equipment can cause serious accidents and death

## **Do not stack or hang more projector frames under each other than allowed by the manufacturer**

- Do not exceed the maximum number of stacked or hung units as this may cause the whole system or parts of it to fall down
- Refer to chapter 11. Maximum stacking information
- Ignoring this might cause significant damage to the product and serious accidents or death may result

## **When stacking multiple frames, it is mandatory to use all four stacking bolts and insert them correct and completely**

- If less than four stacking bolts are used, or if they are not inserted correctly or completely, it is not safe to use the system. See chapter 9. Stacking frames

# Manual FRAME-EVO-C40H / C40H-US

---

- The system is statically designed in such a way, that all bolts must be used correctly. Otherwise, parts or the whole system might fall down. This can cause serious accidents and death as well as property damage.

## **When using the adjustment features of the frame, never apply significant force.**

- When using the adjustment features for pan, tilt and yaw of the frame, never apply force. All adjustments shall work smoothly and do not require significant force.
- If significant force is necessary, the cause may be a faulty part or that, the end of the adjustment range has been reached.
- Ignoring this, might cause significant damage to the product and serious accidents may result

## **Always secure the frames to the rigging truss with rigging slings with steel cable insert and shackles (two sets of rigging sling and shackle are mandatory).**

- The frames must always be secured with two appropriate rigging slings and shackles so that in case of a malfunction it doesn't fall more than 10 cm. It is mandatory to use two sets of rigging slings and shackles to avoid too much dynamic forces as well as the projector swinging. Please consult the local laws or regulations regarding the additional safety of hanging equipment.
- It is important to use correct rigging slings with cable inserts and shackles that are capable to resist the high dynamic forces.
- The rigging slings and shackles act as a secondary safety element and it is mandatory to use them. Not using them or using the wrong products might cause serious accidents and death.

## **Service work shall only be done by qualified personnel that is authorized by the manufacturer. Furthermore, only original spare parts shall be used.**

- Unauthorized personnel shall never do service work on the products, as service work requires special training and knowledge
- Spare parts must always be original ones, provided by the manufacturer
- Not observing these rules on service work ends with immediate effect the responsibility of the manufacturer and, where applicable, warranty is irrecoverably lost. The product is no longer safe to use. This may cause serious accidents or death and property damage.

## 2.2 Caution

**Before installing the projector into the FRAME-EVO-C40H / C40H-US frame, please read the projector's user manual. When the projector has a lens attached, please remove it.**

- The FRAME-EVO-C40H / C40H-US frame with the projector inside must be installed only in an environment that is recommended by the projector manufacturer.
- If this product is not installed correctly, serious accidents may result.

**Minimum two persons are required to install the FRAME-EVO-C40H / C40H-US frame.**

**Additional Lifting accessories like a crane are recommended otherwise more persons will be needed**

- With regard to the overall weight of all necessary installation devices, make sure to handle those with care and use tools for lifting.

**Periodic inspections are mandatory**

- Depending on local laws and regulations owners / users must do periodic inspections of the frame and all components. In case of German regulations this must be done and documented once a year by a qualified and authorised person. Furthermore, for German DGUV V17/V18 is mandatory to revalidate the safety every four years. This must be done and documented by an expert, that is authorized by the German Social Accident Insurance (DGUV)

**Do not place unsecured accessories like tools or electrical devices (converter, video player etc) on top of the frame.**

- These devices may fall down and causes serious accidents or even death to people who are situated near the installation.
- The additional weight of every device added to the system must be considered. Contact the manufacturer for any questions.

**The frame is designed for a static, non-moving, installation.**

- The frame and the installed projector shall not be mechanically or electro mechanically moved around for example for show purposes.

**Use suitable transport boxes / flight cases to protect the system during transport. Handle with care.**

- When transporting the frame with the installed projector, make sure you are using a flight case that protects and damps impacts during transport.

# Manual FRAME-EVO-C40H / C40H-US

---

- Transport shall be carried out gently to avoid damages through falling or similar impacts.
- During transportation, heavy impacts might damage the projector but also the frame. In this case, the stability and safety of the system is at high risk. This can lead to accidents, death and property damage.

## **Use only gentle cleaning agents to avoid damage**

- Cleaning may be done with a soft cloth and a little bit of warm, slightly soapy water
- Do not use any oil, acid etc. on the frame or its components. This may damage the system.

## **Incorrect disposal is a risk to humans and nature**

- Disposal must be done in accordance with local laws and regulations. Contact the manufacturer in case of any questions.

## **2.3 Risk Situations**

### **Risk of injury due to the possibility of falling objects during the assembly or disassembly of the FRAME-EVO-C40H / C40H-US frame.**

- Protection objective: avoid injury from falling parts.
- Wear appropriate safety shoes, gloves and helmet.
- Make sure the area under the frame is clear during installation.

### **Risk of hitting the head with the FRAME-EVO-C40H / C40H-US frame during the hanging set up process.**

- Protection objective: avoid injury from hitting the head.
- Wear a helmet

### **Incorrect installation may lead to certain parts of the FRAME-EVO-C40H / C40H-US frame or the entire FRAME-EVO-C40H / C40H-US frame to fall down.**

- Protection objective: prevent personal injury and property damage.
- Double check the FRAME-EVO-C40H / C40H-US frame and its installation.

### **Insufficient load capacity of the supporting structure may lead to certain parts of the FRAME-EVO-C40H / C40H-US frame or the entire FRAME-EVO-C40H / C40H-US frame to fall down.**

# Manual FRAME-EVO-C40H / C40H-US

---


- Protection objective: prevent personal injury and property damage.
- Provide adequate dimensioning of the supporting structure. The supporting structure must be able to support the combined weight of all the equipment attached to, or hung from it
- Ensure correct installation of the supporting structure.

## Usage of unsafe ladders/steps/scaffolding may lead to serious personal injuries

- Protection objective: prevent personal injury by using only safe ladders/steps/scaffolding.
- Use only appropriate and safe equipment
- Always follow the documentation of the manufacturer of the provided ladders/steps/scaffolding
- Use personal safety equipment if necessary

## The fingers or the hand of the user can be caught between the outer rings and the plates or projector.



- Protection objective: prevent personal injury by using safety gloves.
- When the adjustment of the image is made, the user must always keep his hands on the hand levers (see picture below)



## 3. Scope of delivery



Note: Please check the delivery for completeness and damage immediately after you receive the shipment. Please contact your vendor in case of missing or damaged parts.

	<p><b>FRAME-EVO-C40H / C40H-US</b></p> <ul style="list-style-type: none"><li>• Used for projector installation</li><li>• Number of units: <b>1</b></li><li>• Weight: <b>35 kg / 77,16 lbs</b></li></ul>
	<ol style="list-style-type: none"><li>1) <b>4 x M12x30 ISO 7380 screws</b> (galvanized steel 10.9)</li><li>2) <b>4 x Ø12 Ripp Lock safety washer</b></li></ol> <p><b>Used to secure the projector into the frame.</b></p>
	<p><b>User manual and installation guide</b> for FRAME-EVO-C40H / C40H-US</p>

## 4. Overview of model numbers

### 4.1 FRAME-EVO-C40H / C40H-US designation

European market	Non-European market
Manufacturer m.no.: FRAME-EVO-C40H	Manufacturer m.no.: FRAME-EVO-C40H-US

m.no. = model number

## 5. Optional Accessories

Please refer to chapter “10. Mounting the frame on a truss” and the following for information regarding the usability of the optional accessories.

Note: All clamps are made for 50mm diameter pipes / trussing. Contact us if you need different diameter.

	<p><b>EVO-LINK-350</b></p> <p>Optional accessory for truss mount installations.</p> <p><i>More information can be found in the EVO-LINK-350 series installation manual.</i></p>
	<p><b>FRAME-PF-UNI-CLP5040</b></p> <p>Optional accessory for hanging one FRAME-EVO-C40H / C40H-US</p> <p>FRAME-PF-UNI-CLP5040 represents a complete set of 4 pieces.</p> <p><i>More information can be found in the CLP5040 installation manual.</i></p>

	<p><b>FRAME-PF-UNI-CLP40PT</b> Optional accessory for portrait mode table installation FRAME-PF-UNI-CLP40PT represents a complete set of 4 pieces <i>More information can be found in the CLP40PT installation manual.</i></p>
	<p><b>FRAME-PF-UNI-PORAD-XL-40</b> Optional accessory for portrait mode hanging Usually in combination with EVO-LINK-350 <i>More information can be found in the PORAD installation manual.</i></p>
	<p><b>EVO-LINK-SK</b> Safety Cable Kit used as secondary safety device. The EVO-LINK Safety Cable Kit consists of two 2m lifting straps and two shackles.</p>



The optional accessories must be purchased separately. They are not included in the standard package!



Make sure to not exceed max. weight loads for ceiling mounting.



Always secure the frames to the rigging truss with rigging slings with steel cable insert and shackles (two sets of rigging sling and shackles are mandatory). A potential accessory offered by EXACT solutions is the EVO-LINK-SK. See above table for further details.



Make sure to use only approved and recommended accessories to mount (hanging or standing) the EVO-FRAMEs

## 6. Description of the product

### 6.1 Intended use

The FRAME-EVO-C40H / C40H-US is a frame that is designed and intended for the protection and easy handling of a professional projector installed inside. The FRAME-EVO is guarding highly expensive devices during handling. Furthermore, it offers possibilities to adjust the projector within the frame. Optional accessories can be attached to the frame for example to hang it from a truss or place it on the floor. The FRAME-EVO series is intended for use by fully qualified, trained and competent persons to provide safe and secure transportation, installation and adjustment of projectors. The frame, as well as the projectors that can be installed, are made only for indoor usage.

### 6.2 Specifications

Parameter	Value
Size [mm]	See drawing
Weight [kg] Frame only	35 kg
Maximum projector weight incl. lens	110 kg <i>Note:</i> <i>Griffyn weight is approx.: 100 kg</i> <i>Heaviest lens approx.: 10 kg</i>
Overall system weight (Projector, heaviest lens, frame)	Approx. 145 kg
Operating temperature [°C]	0 - 45
Operating rel. humidity [%rH]	10 - 75
Operation area	Indoor in closed rooms

## 7. Installing the projectors into the frame



Make sure that only the designated projectors are installed into this frame! Do not try to use it with other projectors because serious accidents can occur!

**Step 1:** Place the projector upside down on a suitable flat surface then remove the lens (if it is pre-installed). It is recommended to place an appropriate material underneath the projector, so that it is lifted up by about 10 cm. This will help during the installation process.




Figure 3 Mounting the projector into the frame

**Step 2:** Please put the projector in the right position so that the front/back position is correct when installing. The lens of the projector has to be at the front of the frame, the front of the frame is where the two lever handles are located (see pointing hand in above figure). Now align the M 12 threads of the projector bottom side with the corresponding screw holes of the frame plate (marked with red circles in above figure).




Figure 4 Securely tighten all screws

**Step 3:** Place the 4 x Ø12 Rip Lock safety washer (2) over each corresponding hole. Secure the 4 x M12x30 ISO 7380 screws (1) into each hole with 13,56 to 16,95 Nm (120 to 150 in-lbs) torque. Ensure each screw runs through the plate and catches into the corresponding M12 thread in the projector surface. Please make sure to use only the correspondent screw holes when installing a projector!



Do not forget to use all of the 4 x Ø12 Rip Lock safety washer (2) as they are preventing the screws to loosen themselves!



Make sure you tighten all of the four screws with the correct torque of 13,56 to 16,95 Nm (120 to 150 in-lbs)



The torque value had been provided by the projector manufacturer.

**Step 4:** The lens can be attached back to the projector.

## 8. Adjustment options



Figure 5 Illustration of yaw, pitch and roll




Figure 6 Adjustment: Roll

### Roll

Using the hand levers to the left and right you can adjust the position of the projector with an angle of  $\pm 2.6$  degrees.

You can lower or lift the front left or right corner.

To roll the projector around the center axis, the two hand levers must be turned in opposite directions.



Figure 7 Adjustment: Pitch

### Pitch

Also by using the two hand levers at the sides, you can lower the projector by an angle of  $-1,58$  degrees and lift it by an angle of  $+2,08$  degrees.



## Yaw

By turning the adjustment screw below the projector, you can move the back of the projector to the left or to the right by an angle of  $\pm 2,5$  degrees.

Figure 8 Adjustment: Yaw



When adjusting Roll/Pitch/Yaw, always keep your hands on the hand levers.

## 9. Stacking frames




Figure 9 Stacking frames

**Step 1:** Place the upper frame with mounted projector on top of the lower frame with mounted projector. Make sure the four male bolts enter into the correspondent female bolts. To secure, insert the locking pins through the holes in the female bolts. Always make sure that the locking pins are locked after being inserted



When stacking the frames, make sure that all four locking pins pass completely through the female stacking bolt and that they are secured.

## 10. Mounting the frame on a truss



Figure 10 Threaded holes on bottom side of frame

To hang the frame on a truss one must use all of the **4 x M8** and the **4 x M10** threaded holes to attach a mounting accessory like the **EVO-LINK-350 series**. Overall 8 screw holes have to be used. Use only the original and recommended accessories for this procedure. Make sure the trussing or supporting structure is capable of carrying the overall weight.



Insufficient load capacity of the supporting structure may lead to certain parts of the FRAME-EVO-C40H / C40H-US frame or the entire FRAME-EVO-C40H / C40H-US frame to fall down.



Always secure the frames using appropriate **rigging slings with steel cable insert and shackles**. Make sure they are chosen correctly regarding strength, format and length. Please avoid high dynamic forces by ensuring that the frame will not drop more than **10 cm** into the rigging slings. A potential accessory offered by EXACT solutions is the EVO-LINK-SK. See also chapter 5. Optional Accessories.



Please consult the local laws or regulations regarding the additional safety of hanging equipment.

# Manual FRAME-EVO-C40H / C40H-US

---

When using the EVO LINK Safety Kit, it is important that the rigging sling is double-wrapped and used in a basket hitch configuration to secure the load. By this overall four strings of the rigging sling carry the potential weight. Figure 11 illustrates the correct usage. Figure 12 shows the usage with the frame.




Figure 11 Illustration of basket hitch with a double wrapped rigging sling





Figure 12 Securing one frame with two sets of rigging slings



The rigging slings should always be installed as a basket hitch. The sling cradles the load and both ends are connected with the shackle.



The two rigging slings must be installed in the same way. This ensures that when the load falls into the rigging slings, both will carry the load.



*Figure 13 Securing two frames with two sets of rigging slings*



When hanging two frames under each other, secure all frames with the rigging slings. Securing only the upper frame or only the lower frame is not sufficient! Figure 13 shows two frames hanging from a truss where both are secured with rigging slings (Note: The frames are without projector for illustration purpose)



For further information regarding an appropriate rigging sling with steel cable insert and shackle please contact us. A potential accessory offered by EXACT solutions is the EVO-LINK-SK. This is a Safety Cable Kit used as secondary safety device. The EVO-LINK Safety Cable Kit consists of two 2m lifting straps and two shackles. See also chapter 5. Optional Accessories.



When using EVO-LINK-SK or other solutions to act as a secondary safety device make sure that the load will not fall more than 10cm to avoid dynamic forces. Depending on the installation, additional material like shackles might be necessary.

## 11. Maximum stacking information

Please refer to the tables below to confirm proper usage.




Do not try to setup the frame in another position than that presented, because accidents can occur!

Hanging installation with EVO-LINK-350 series		
	1	2
Landscape		

## With rigging clamps FRAME-PF-UNI-CLP5040


Portrait



Distance between the rigging clamps:

- On X axis: 498 mm
- On Y axis: between 160 mm and 467 mm

Landscape




Distance between the rigging clamps:

- On X axis: 788,5 mm
- On Y axis: between 160 mm and 467 mm



**Warning:** hanging more than **one** projectors with the rigging clamp is not possible! Please do not try to hang more than **one** projector with the rigging clamps because mechanical failure and accidents can occur.

Vertical Down



Distance between the rigging clamps:

- On X axis: between 240 mm and 538 mm
- On Y axis: 498 mm

# Manual FRAME-EVO-C40H / C40H-US

## With Portrait Adapter FRAME-PF-UNI-PORAD-XL-40 together with EVO-LINK-350 series

Portrait



- More information can be found in the FRAME-PF-UNI-PORAD-XL installation manual.

Vertical  
Down



- More information can be found in the FRAME-PF-UNI-PORAD-XL installation manual.



Warning: When using rigging clamps make sure that they are mounted centred. This makes sure that the weight of the frame and projector is equally distributed between all clamps and to the projector frame.




Warning: When using a Portrait Adapter make sure that it is mounted centred. This makes sure that the weight of the frame and projector is equally distributed between all clamps of the portrait adapter and to the projector frame.



Note: Above pictures show EVO-LINK 350. When this manual was written, EVO-LINK 350 was not ready for market yet so the final product may differ from what is illustrated and named here

## Standing on a floor

Portrait




In this position one must use the **FRAME-PF-UNI-CLP40PT** and the frame has to be positioned with the **adjustment screw** on top.

Landscape


1



2



3



## 12. System maintenance and inspection (Re-examination)



The FRAME-EVO-C40H / C40H-US does not require special maintenance but a visual inspection must be done **prior to every installation** in which the system is involved. The inspection must be done by a qualified person!



**Periodic inspections are mandatory.** Depending on local laws and regulations owners / users must do periodic inspections of the frame and all components. In case of German regulations this must be done and documented once a year by a qualified and authorised person. Furthermore, for German DGUV V17/V18 it is mandatory to revalidate the safety every four years. This must be done and documented by an expert that is authorized by the German Social Accident Insurance (DGUV).



Note: The necessary inspection can also be done by the manufacturer.

### 12.1 Mounting threads at bottom side




Figure 14 Inspection of mounting threads at bottom side

- Before and after each installation, the **M8 and M10 mounting holes** (see red marking in Figure 14, circular markings are for M8, rectangular markings are for M10) must be carefully inspected, as they may get damaged during the installation of the hanging accessory.
- Please carefully examine the M8 and M10 mounting holes by checking each one of them and make sure the thread is not broken or damaged in any way.


## 12.2 Sealed nuts with red coloured wax and other screw connections

- Please make a visual inspection to be sure that all the screws are in the right place and none are missing.
- Make sure that the screws, nuts, stacking pins, connection rods, mounting plate and all the components are not bended, damaged, or broken.




If any parts are broken or missing stop using the product, please contact the seller so he can provide the spare parts.

Bottom view:



*Figure 15 Nuts on front bottom side which are sealed with red colour wax*

Top view:



*Figure 16 Nut on centre top side which is sealed with red colour wax*

- On the three screws + nuts presented on the above two pictures (Figure 17 and Figure 16) red color sealing wax was applied to be sure that the nuts will always be on the same position and no one will try to tighten or loose them.



Do not try to manipulate these nuts, because the adjustment mechanism can be blocked and accidents can occur!



If one notices that the sealing wax is broken or the nut is moved stop using the product, please contact the manufacturer!

Except for the three nuts described on the previous section (see Figure 17 and Figure 16), please control, with corresponding tool, that all the other screws are properly tightened.

## 12.3 Stacking points and locking pins

Make sure that all stacking points (four male stacking points on upside of the frame and four female stacking points on bottom side of the frame) are securely tighten in their position. This can be checked by hand, no extra tools are required. Also check that the stacking points do not show any damages such as dents, bending etc.

The two figures below show with red marking the stacking points at the topside (left picture) and the ones at the bottom side (right picture).



Figure 17 Stacking points topside



Figure 18 Stacking points bottom side



If one notices that the stacking points are not securely tighten or show any sort of damage, stop using the product and contact the manufacturer.

Make sure that all four locking pins are available next to the female stacking points at the bottom side of the frame. It is mandatory to use all four locking pins when frames are stacked (see also chapter 9. Stacking frames).



Figure 19 Locking pins at the frame

Make sure that all four locking pins do not show any sort of damage such as being bent, deformed or that no piece is missing (e.g. the ball spring). Furthermore ensure by testing the locking mechanism that it works fine. The locking mechanism is activated by pressing the back side of the locking pin. With this, the ball spring at the front should slide into the housing of the pin. Releasing the mechanism will make the ball spring slide back out. It is important that this works smoothly. The ball spring secures the locking pin inside its designated position.




Figure 20 Locking pin – the ball spring



Do not keep using a frame with damaged or faulty working locking pins! Contact the manufacturer!




Do not exchange broken or malfunctioning parts with ones that are not accredited by the manufacturer because serious injuries and property damage can occur!



The inspection must be done by a qualified person!

## 12.4 Screws and safety washers securing the projector in the frame



Make sure all correct screws and safety washers are in the correct position and securely fasten. For further details see chapter 7. Installing the projectors into the frame.

## **13. Disposal of components**

### **13.1 Metal parts and packaging**

All metal parts and packaging can be recycled.

### **13.2 Disposal of entire devices**

You have the possibility to send old devices back to us. Please note that you have to take over the transportation costs for this. Please send the devices to:

EXACT solutions GmbH

Lustheide 85

51427 Bergisch Gladbach

GERMANY

## 14. Declaration of Conformity



### EC - Declaration of Conformity

We hereby confirm that the following described lifting accessory in its conception, construction and form put by us in circulation is in full accordance with all relevant health and safety requirements and complies with the following EC-directive:

**2006 / 42 / EG (EG-Machinery Directive)**

This declaration is no longer valid if the lifting accessory is modified without our written consent.

**Manufacturer:**

EXACT solutions GmbH  
Lustheide 85  
D-51427 Bergisch Gladbach  
Tel.: +49 2204 9485 30

**Description of the lifting accessory:**

- Function: Rigging frame for Christie projectors series such as: Griffyn Series and other compatible projectors.
- Type/model: FRAME-EVO-C40H or FRAME-EVO-C40H-US
- Serial number: FE-C40HXX.YYYYYY or FE-C40HXXUS.YYYYYY
- Year of construction: 2024

**The applied harmonized EN - standards include:**

- **DIN EN ISO 1200:2010** Safety of machinery – General principles for design – Risk assessment and risk reduction

**Further applied standards and regulations include:**

- **DIN EN 1991-1** DE: Eurocode 1: Einwirkungen auf Tragwerke (12/2010)  
EN: Eurocode 1: Actions on structures (12/2010)
- **DIN EN 1993 -1** DE: Eurocode 3: Bemessung und Konstruktion von Stahlbauten (12/2010)  
EN: Eurocode 3: Design of steel structures (12/2010)
- **DIN EN 1999 -1** DE: Eurocode 9: Bemessung und Konstruktion von Aluminiumtragwerken (05/2010)  
EN: Eurocode 9: Design of aluminum structures (05/2010)
- **DGVV V17/18** DE: UVV Veranstaltungs- und Produktionsstätten für szenische Darstellung, Stand Januar 2011 (bisher: BGV C1)  
EN: Accident Prevention Regulation for Staging and Production Facilities for the Entertainment Industry (formerly BGV C1)
- **DGVV 315-390** DE: Grundsätze für die Prüfung maschinentechnischer Einrichtungen in Bühnen und Studios (bisher: BGG/GUV-G 912)  
EN: Fundamentals for testing in stages and studios of the mechanical equipment (formerly BGG/GUV-G 912)
- **BGI 810-3** DE: Lasten über Personen. Sicherheit bei Produktionen und Veranstaltungen von Fernsehen, Hörfunk, Film, Theater, Messen, Veranstaltungen  
EN: Safety at Productions and Events – Loads Suspended above Persons
- **DIN EN 62368-1** DE: Einrichtungen für Audio/Video-, Informations- und Kommunikationstechnik Teil 1: Sicherheitsanforderungen  
EN: Audio/video, information and communication technology equipment Part 1: Safety requirements

Bergisch Gladbach, 20th of November 2024

Signature:

(Tobias Schwirten, Managing Director, EXACT solutions GmbH)



## Imprint

EXACT solutions GmbH

Lustheide 85

51427 Bergisch Gladbach

GERMANY

Tel.: +49 2204 9485 30

E-Mail: [info@exactsolutions.de](mailto:info@exactsolutions.de)

Web: [www.exactsolutions.de](http://www.exactsolutions.de)