

# Christie Roadie 4K Series



Auditoriums  
Houses of worship  
Large venues

Location-based entertainment  
Projection mapping  
Rental staging



## Christie TruLife 4K projection – built tough

Now you can bring 4K, 60Hz projection on the road with the Christie® Roadie 4K ruggedized projectors. Engineered to withstand the rigors of the road and other demanding applications, the Christie Roadie 4K35 and Roadie 4K45 feature industry-leading Christie TruLife™ electronics. Capable of supporting 1.2Gpx/s operation and equivalent 25-bits processing, TruLife enables astonishing color reproduction, full connectivity – including 3G-SDI – and built-in image warping and blending.

Utilizing proven Xenon illumination, these high brightness, 3-chip DLP® projectors are available in 35,000 and 45,000 lumen models and are upgradable to true 120Hz operation. Utilizing the optional robust rigging and stacking frame, these powerful projectors are perfect for large-scale visual spectacles such as live events, location based entertainment and projection mapping.

**CHRISTIE®**

		Christie Roadie 4K35	Christie Roadie 4K45
Image	brightness	• 32,500 ANSI lumens - (35,000 center lumens)	• 43,000 ANSI lumens - (45,000 center lumens)
	contrast	• 2000:1	
Display technology	type	• 3-chip 1.38" DMD	
	native resolution	• Native 4K (4096 x 2160)	
Lamp	type	• Xenon bubble	
	estimated life	• 6.0kW CDXL-60 - 750hrs • 4.5kW CDXL-30 - 900hrs • 3.0kW CDXL-20 - 2500hrs • 2.0kW CDXL-20 - 3500hrs	• 7.0kW CDXL-70 - 350hrs • 6.0kW CDXL-60 - 750hrs • 4.5kW CDXL-30 - 900hrs • 3.0kW CDXL-20 - 2500hrs • 2.0kW CDXL-20 - 3500hrs
Input	signals	• 2 x Dual 3G HD-SDI input card • 2 x Twin display port input card	
	pixel clock	• 1.2Gpx/s - TruLife Electronics	
Inputs/outputs, control and networking	input	• RS-232 In • Ethernet (10/100) RJ-45 with ChristieNET™ connectivity • Detachable control panel	
Lens mount		• Tool-free lens insertion system • Boresight adjustable • Motorized horizontal and vertical lens offset • Motorized zoom and focus adjustment	
Lenses	fixed	• 0.72:1* • 1.0:1**	
	zoom	• 1.13-1.31:1*** • 1.31-1.63:1 • 1.63-2.17:1 • 1.98-2.71:1 • 2.71-3.89:1 • 3.89-5.43:1 • 5.43:1-7.69:1***	
	offsets	• All lenses ± 13% Vertical ± 4% Horizontal except those noted below * No offset ** 1.0:1 fixed lens Vertical: ± 29% Horizontal: 9% ***1.13-1.31:1 zoom lens Vertical: ± 56% Horizontal: 19%	
Accessories	standard	• Ballast and cables • Wired TPC • User manual	
	optional	• Dual link DVI input card • Twin HDMI input card • Rigging and stacking frame	
Power requirements	operating voltage	• Single phase 200-240 VAC @ 50/60Hz	
	operating current	• 7A @ 200V	
	ballast	• Type: detached, 8kW low-ripple, switch-mode lamp ballast • Operating voltage: 3-phase 200-230 VAC @ 50/60Hz • Current: 39A per phase max • Operating voltage: 3-phase 380-415 VAC @ 50/60Hz • Current: 26A per phase max	
Physical	size (no feet, no lens)	• Head (LxWxH): 52.3 x 25.5 x 20.53" (1329 x 647 x 522mm) • Ballast (LxWxH): 21.34 x 17.52 x 20.93" (542 x 445 x 532mm)	
	shipping size	• Head (LxWxH): 55.98 x 35.98 x 31.50" (1422 x 914 x 800mm)	
	weight	• Head 284.4lbs (129kg) no lens, no linecord • Ballast 126lbs (57kg)	
	shipping weight	• Head 352.7lbs (160kg) • Ballast 156.5lbs (71kg)	
Environment	operating temperature	• 40-104°F (5-40°C)	
	operating humidity	• 0-90% non-condensing	
Regulatory approvals		• This product conforms to the following regulations related to product safety, environmental requirements and electromagnetic compatibility (EMC) Directives: (EC) 2011/65/EU (RoHS) • 2012/19/EU (WEEE) • Regulations: (EC) No. 1907/2006 (REACH) • CAN/CSA C22.2 No. 60950-1 • UL 60950-1 • IEC 60950-1 • EN 60950-1 • FCC, Part 15, Subpart B, Class A • EN55022/CISPR22 Class A • EN55024/CISPR24	
Warranty	projector	• Three years parts and labor limited warranty (including light engine)	
	lamp	• Contact an authorized Christie representative for the full details of our limited warranty	

United Kingdom  
Branch & EMEA  
Head Office  
ViewPoint  
200 Ashville Way  
Wokingham  
Berkshire, U.K.  
RG41 2PL  
PH: +44 (0) 118 977 8000

Middle East  
Light Industrial Unit (LIU-17)  
Nad Al Shibba  
Sheikh Mohammed Bin Zayed Road  
Dubai Silicon Oasis  
PO Box: 293762  
Dubai - U.A.E  
PH: +971 (0) 4 503 6800

Africa  
Unit C3  
Northlands Deco Park  
New Market Road  
Northriding  
Randburg  
2164  
Johannesburg  
Gauteng  
South Africa  
PH: +27 71 335 8667

#### Other EMEA offices

Germany  
Branch Office  
PH: +49 2161 566 200

France  
Branch Office  
PH: +33 (0) 1 41 21 44 04

Eastern Europe  
Representative Office  
PH: +36 (0)1 47 48 138

Spain  
Branch Office  
PH: +34 91 633 9990

Italy  
Independent Sales Consultant Office  
PH: +39 (0) 2 9902 1161

Russia  
Independent Sales Consultant Office  
PH: +7 (495) 930-8961



For the most current specification information, please visit [www.christieemea.com](http://www.christieemea.com)

Copyright 2016 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4004 Jan 15

**CHRISTIE®**