

Christie Boxer 4K20 and 4K30

		Christie Boxer 4K20 144-011103-01	Christie Boxer 4K30 144-001012-03
Image	brightness	<ul style="list-style-type: none"> • 19,500 ANSI (typical) • 20,000 Center • 22,000 ISO 	<ul style="list-style-type: none"> • 29,000 ANSI (typical) • 30,000 Center • 32,500 ISO
	contrast	• 2000:1	
Display technology	type	• 3DLP® 1.38" DMD	
	native resolution	• 4K (4096 x 2160)	
Lamp	type	• 4 x 450W NSH	• 6 x 450W NSH
	life	• 1500 hrs to 70% initial brightness, and up to 2500 at 50%	
Inputs	standard	<ul style="list-style-type: none"> • 1 x High bandwidth multi-input card (HBMIC) <ul style="list-style-type: none"> - 2 x 12G-SDI - 1 x HDMI 2.0 - 1 x DisplayPort 1.2 - 1 x Fiber (QSFP+) for use with Christie® Link Transmitter - HDBaseT 	
Pixel clock		• 1.2Gpx/s - Christie TruLife Electronics	
Networking		<ul style="list-style-type: none"> • Keypad • RS232 in • Ethernet (10/100) RJ45 	
Lens mount		<ul style="list-style-type: none"> • Tool-free lens insertion system • Boresight adjustable • Motorized horizontal and vertical lens offset • Motorized zoom and focus adjustment 	
Lenses	fixed	<ul style="list-style-type: none"> • 0.72:1 (no offset) • 0.9:1 (offset: V: ±45%, H: ±15%) 	
	zoom	<ul style="list-style-type: none"> • 1.13-1.31:1 (offset: V: ±60%, H: 25%) • 1.31-1.63:1 (offset: V: ±80%, H: 30%) • 1.63-2.17:1 (offset: V: ±80%, H: 30%) • 1.99-2.71:1 (offset: V: ±15%, H: 5%) • 2.71-3.89:1 (offset: V: ±45%, H: 15%) • 3.89-5.43:1 (offset: V: ±85%, H: 25%) • 4.96:1-7.69:1 (offset: V: ±55%, H: 20%) 	
Optional accessories		<ul style="list-style-type: none"> • Dual link DVI input card • Twin HDMI™ input card • Quad DisplayPort input card (slot 0 only) • Christie Link Transmitter (Fiber) • Dual 3G HD-SDI input card • Twin DisplayPort input card • Rigging and stacking frame 	
Power requirements	operating voltage	• 200-240V	
	operating current	• 19A	
Dimensions	size	• (LxWxH): 37.75 x 23.5 x 12" (959 x 597 x 305mm)	
	weight	• 160lbs (72.57kg)	
Operating environment	temperature	• 41-104°F (5-40°C)	
	humidity	• 10-80%, non-condensing	
Warranty		• Three years	

For Christie Boxer 2K20 and 2K30 specs, please visit christiedigital.com.

United Kingdom
Branch & EMEA
Head Office
ViewPoint
200 Ashville Way
Wokingham
Berkshire, U.K.
RG41 2PL
PH: +44 (0) 118 977 8000

Middle East
Light Industrial Unit (LIU-17)
Nad Al Shibba
Sheikh Mohammed Bin Zayed Road
Dubai Silicon Oasis
PO Box: 293762
Dubai - U.A.E
PH: +971 (0) 4 503 6800

Africa
Unit C3
Northlands Deco Park
New Market Road
Northriding
Randburg
2164
Johannesburg
Gauteng
South Africa
PH: +27 11 251 0000

Other EMEA offices

Germany
Branch Office
PH: +49 2161 566 200

France
Branch Office
PH: +33 (0) 1 41 21 44 04

Spain
Branch Office
PH: +34 91 633 9990

Italy
Independent Sales Consultant Office
PH: +39 (0) 2 9902 1161

Russia
Independent Sales Consultant Office
PH: +7 (495) 930-8961



For the most current specification information, please visit www.christieemea.com

Copyright 2017 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4481 Mar 17

CHRISTIE®