

CHRISTIE GS SERIES DWU850-GS / DHD850-GS

Auditoriums | Boardrooms | Conference rooms | Education spaces
Government | Hotels | Museums | Worship facilities

Performance and reliability for high-usage environments

Avoid downtime, cost of lamp replacements and maintenance by choosing the Christie® DHD850-GS or DWU850-GS solid state illumination projectors for your next project. From business venues to events and beyond, professional-grade Christie GS Series models deliver great performance and reliability in high-usage environments.

Enjoy bright and vibrant visuals in all environments thanks to Christie RealBlack™ technology advancements. DHD850-GS or DWU850-GS projectors provide 20,000 hours and up to 8,400 lumens of low-cost operation. Wireless connectivity, built-in warping and blending, lightweight, quiet operation and a full suite of lenses make the GS Series models ideal for boardrooms, conference rooms, education, worship facilities, hotels and other small and medium venues.



CHRISTIE®

Technical specifications		Christie DWU850-GS	Christie DHD850-GS	
Image	brightness	<ul style="list-style-type: none"> • 8400 ISO lumens (typical) • 7500 ANSI lumens (typical) 	<ul style="list-style-type: none"> • 7750 ISO lumens (typical) • 6900 ANSI lumens (typical) 	
	color wheel	• 4 segment (RGBY) - 2X or 3X speed		
	contrast (full on/full off)	• Full on/off (Christie RealBlack enabled): 300,000:1 • Dynamic Contrast: 6000:1		
Display technology	type	• 1-chip 0.67" DMD		
	native resolution	• 1920 x 1200 (2,304,000 pixels) (16:10)		
	performance	• Features precise software color adjustments for hue, saturation and gain. Adjust the hue of each primary color component (red, green, blue and white) for perfecting images on an individual projector or for matching colors across multiple adjacent displays		
Illumination	type	• Laser phosphor with Christie BoldColor Technology		
	performance	• 20,000 hrs to 50% brightness		
Inputs	standard	<ul style="list-style-type: none"> • HDMI x 2 (HDCP 1.3) (one on side panel, one on bottom) • 3GSDI x 1 (BNC) • DVI x 1 (digital only); VGA x 1 • USB x 1 (Type A); Mini USB x 1 (Type B) • RS232 in • Control via HDBaseT • Ethernet (10/100) RJ45 • Built-in backlit keypad • Wired remote control (3.5mm stereo) - loop out available for daisy chaining 		
	3D	<ul style="list-style-type: none"> • HDMI 1.4, HDBaseT - frame packed, top/bottom, side-by-side/frame sequential (up to 120 Hz) • Up to 120 Hz output • 3D Sync in (BNC) - for genlocking projectors • 3D Sync out (BNC) - for genlocking projectors or controlling emitter polarizer 		
	signals	<ul style="list-style-type: none"> • HDTV formats VGA through to WUXGA (1920 x 1080) • Horizontal and vertical scaling while maintaining aspect ratio (all inputs) 		
	pixel clock	• 162 MHz (1600 x 1200); 154 MHz (1920 x 1200)		
	scan rates	• Horizontal: 15-91kHz • Vertical: 24-120Hz		
	Signal outputs	monitor out	<ul style="list-style-type: none"> • 3GSDI x 1 (BNC) • HDMI x 1 out 	
	Warping and blending		• Embedded warping and blending (no option board required)	
Control and networking		<ul style="list-style-type: none"> • RS-232 in • Control via HDBaseT • Ethernet (10/100) RJ-45 with ChristieNET™ connectivity • Built-in backlit keypad • Wired remote control (3.5mm stereo) - loop out available for daisy chaining 		
Lens mount	type	• Boresight adjustable • Motorized horizontal and vertical lens offset • Motorized zoom and focus adjustment		
Lenses	0.36:1 Fixed UST lens offsets	• Fixed		
	075 - 5.50 TR Lenses offsets	<ul style="list-style-type: none"> • ±100% Vertical (540 pixels) • ±30% Horizontal (288 pixels) 		
	optional	<ul style="list-style-type: none"> • Lens 0.36 (120") Ultra short throw lens • Lens 0.75-0.95 Zoom G/GS • Lens 0.95-1.22 Zoom G/GS • Lens Zoom HP G/GS 1.22-1.52 Zoom G/GS • Lens 1.52-2.89 Zoom G/GS • Lens 2.9-5.50:1 Zoom G/GS 		
Accessories	standard	<ul style="list-style-type: none"> • IR remote with wired remote jack (wire not included) • AC line cord for projector head • User manual • QwikRig Rigging Frame (140-128102-02) • Christie One Mount Plus (140-117100-XX) 		
	optional	<ul style="list-style-type: none"> • Christie One Mount (108-506102-01) • One Mount Extender Rod (121-125109-01) • Wireless dongle (133-113106-01) • One Mount Rigging Kit (used with One Mount, One Mount Plus and/or One Mount Extender Rod) (121-126100-01) 		
Power requirements	operating voltage	• Normal: 100-240 VAC @ 50/60Hz (w/ 15A fuse)		
	power consumption	• Normal mode: 900W		
	operating current	• Normal mode: 9A (100V-240V)		
	dissipation	<ul style="list-style-type: none"> • 3071 BTU/hr (Normal mode) • 1689 BTU/hr (ECO2 mode) 		
Audible noise		• Standard mode: 37dB(A) • Eco2 mode: 34dB(A)		
Physical	size	• (LxWxH): 18.9 x 21.9 x 7.5" (480 x 555 x 190mm) w/o feet or lens		
	shipping size	• (LxWxH): 23.6 x 29.9 x 14.7" (599 x 759 x 373mm)		
	weight	• 52.4lb (23.7kg) w/o lens		
	shipping weight	• 66.3lb (30kg)		
Environment	operating conditions	• 32-104°F (0-40°C) • Humidity: 10-85% non-condensing		
Regulatory		<ul style="list-style-type: none"> • This product conforms to all relevant European directives, standards, safety, health and environmental concerns • Directives: RoHS • REACH • WEEE • Contact Christie for timing of certifications: UL/CSA/IEC 60950-1 • FCC Class A • CE • FDA • CCC • KC • PSE • EAC • BIS • VCCI • RCM • TER 		
Warranty		<ul style="list-style-type: none"> • Three years on the projector • Three years or 20,000 hours on the illumination system¹ • Contact an authorized Christie representative for full details of our limited warranty 		

¹ Reference the Christie Standard Limited Warranty document for details.

For the most current specification information, please visit christiedigital.com

Copyright 2021 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD1828_Christie GS Series_850-GS_Datasheet_Feb 2021

