

Christie

E600 Controller

Technical specifications

Inputs		<ul style="list-style-type: none"> • 1 x DP (HDCP compatible) • 1 x HDMI (HDCP compatible) • 2 x Dual-link DVI1 x BNC SDI-in • 1 x BNC SDI-loop
GenLock		<ul style="list-style-type: none"> • 1 x BNC in • 1 x BNC loop
Outputs		<ul style="list-style-type: none"> • 16 x Neutrik Gigabit Ethernet • 4 x Optical Fiber
Control		<ul style="list-style-type: none"> • 1 x RJ45 Ethernet • 1 x USB-A link-in • 1 x USB-B link-out • 1 x USB-B (front panel)
Accessories		<ul style="list-style-type: none"> • USB cable (1.5m) • HDMI cable (1.5m) • DP cable (1.5m) • Ethernet cable (1.5m)
Power	input rating	• 100-240 VAC @ 50/60Hz
	power consumption	• 30W
	heat output	• 102 BTU/hr
Physical	size	• (LxWxH) 19.0 x 14.6 x 3.5" (482.6 x 370.0 x 89.0mm)
	weight	• 9lbs (4.1kg)
Environment	operating temperature	• -4-140°F (-20-60°C)
	operating humidity	• 10-90%
	storage temperature	• -14-122°F (-26-55°C)
Warranty		<ul style="list-style-type: none"> • Three year parts and labor limited warranty • Contact an authorized Christie representative for full details of our limited warranty

Performance specifications are typical. Due to constant research, specifications are subject to change without notice.

For the most current specification information, please visit christiedigital.com

Copyright 2021 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and other countries. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.

CD1834_Christie_E600_Controller-Specsheet_Mar 2021 EN



CHRISTIE[®]