

# Christie Velvet - Apex Series

## 2.5mm indoor LED tiles - landscape


Technical specifications		Christie LED025-AL
Display technology	pixel pitch	• 2.56mm
	pixel configuration	• 3-in-1 (1R1G1B)
	pixel density	• 152,100 pixels/m <sup>2</sup>
	maximum calibrated brightness	• 1000 nits (cd/m <sup>2</sup> )
	aspect ratio	• 16:9
	contrast ratio (full field)	• 5000:1
	viewing angle	• 160° H, 140° V
	refresh rate	• ≥3200Hz
	scan rate	• 1/15
	color temperature	• 2700-9600K
Signal	display colors	• 4.398 trillion (14-bit)
	inputs	• HDMI (HDCP) • DVI (HDCP) • HDSDI
Power	input rating - remote power supply <sup>1</sup>	• 100-240 VAC @ 50-60Hz
	power consumption per cabinet	• 32W typical • 96W maximum
	heat output	• 109 BTU/hr typical • 328 BTU/hr maximum
Environment	operating temperature	• 32-104°F (0-40°C)
	operating humidity	• 10-90% non-condensing
	storage temperature	• 14-122°F (-10-50°C)
	environment	• Indoor
	IP rating	• 30
	LED lifespan (50% brightness)	• 100,000 hrs
	runtime	• 24/7
Physical	tile dimensions (installed)	• (WxHxD): 24.19 x 13.61 x 3.71" (614.4 x 345.6 x 94.3mm)
	tile area	• 2.29 ft <sup>2</sup> (0.2123m <sup>2</sup> )
	tile resolution	• 240 x 135 pixels
	tile weight	• 19.8lbs (9kg)
	cabinet design	• Die-cast aluminum
	service access	• Front service only
	module dimensions	• (WxH): 6.05 x 4.54" (153.6 x 115.2mm)
	module resolution	• 60 x 45 pixels
	support brackets & blocks	• included
Certifications <sup>2</sup>	• UL, FCC, CE, EMC, RoHS	
Warranty	<ul style="list-style-type: none"> <li>• Three year parts and labor limited warranty</li> <li>• Contact an authorized Christie representative for full details</li> <li>• Extended warranty option available for a one-time fee at time of purchase</li> </ul>	

<sup>1</sup>See remote power supply specifications for full details.


<sup>2</sup>Certain of the listed certifications may be pending and not yet issued. For the current status of the listed certifications, please contact an authorized Christie representative.

Performance specifications are typical. Due to constant research, specifications are subject to change without notice.


### Front view



### Back view



### Side view



**United Kingdom**  
Branch & EMEA  
Head Office  
ViewPoint  
200 Ashville Way  
Wokingham  
Berkshire, U.K.  
RG41 2PL  
PH: +44 (0) 118 977 8000

**Middle East**  
Light Industrial Unit (LIU-17)  
Nad Al Shibba  
Sheikh Mohammed Bin Zayed Road  
Dubai Silicon Oasis  
PO Box: 293762  
Dubai - U.A.E  
PH: +971 (0) 4 503 6800

**Africa**  
Unit C3  
Northlands Deco Park  
New Market Road  
Northriding  
Randburg  
2164  
Johannesburg  
Gauteng  
South Africa  
PH: +27 71 335 8667

### Other EMEA offices

**Germany**  
Branch Office  
PH: +49 2161 566 200

**France**  
Branch Office  
PH: +33 (0) 1 41 21 44 04

**Eastern Europe**  
Representative Office  
PH: +36 (0)1 47 48 138

**Spain**  
Branch Office  
PH: +34 91 633 9990

**Italy**  
Independent Sales Consultant Office  
PH: +39 (0) 2 9902 1161

**Russia**  
Independent Sales Consultant Office  
PH: +7 (495) 930-8961

For the most current specification information, please visit [www.christieemea.com](http://www.christieemea.com)



Copyright 2016 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4334 Aug 16

**CHRISTIE®**