Christie MicroTiles LED

storage temperature

Certifications

Warranty

environment

Christie Link E1000 Wall Controller

Technical specifications Christie Link E1000 • 2 x DP 1.2 (HDCP compatible) Inputs: sync in • 2 x HDMI 2.0 (HDCP compatible) Outputs: Sync out • 2 x QSFP+ 40Gb (Bi-directional) Control • 1 x RJ45 Ethernet • USB (RS232 via dongle) • 100-240 VAC @ 50/60Hz input rating Power power • 30W consumption heat output • 102 BTU/hr • Optional rackmount kit available • (LxWxH): 11.2 x 8.7 x 1.7" (285.5 x 220.2 x 42.8mm) Physical size • 1.5kg weight installation options • Optional rackmount kit available Environment operating • 32-104°F (0-40°C) temperature • 10-90% RH non-condensing operating humidity • 14-122°F (-10-55°C)

UL60950, FCC, CE, EMC, RoHS, RC2

a one-time fee at time of purchase

• Three year parts and labor limited warranty, extended warranty option available for



• Indoor

← Christie Link E1000



For the most current specification information, please visit christiedigital.com

Copyright 2023 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD4044-Christie-Link-Controller-SpecSheet-Oct-23





