

Christie MicroTiles LED

Christie Link video wall controller

Technical specifications		Christie Link E1000 / E1000-3D	Christie Link E1100
Inputs		<ul style="list-style-type: none"> • 2 x DP 1.2 (HDCP compatible) • 2 x HDMI 2.0 (HDCP compatible) 	<ul style="list-style-type: none"> • Quad 3G-SDI (4 port) or 3G-SDI (1 port) • 1 x SDVoE (10Gb SFP+)
Outputs		<ul style="list-style-type: none"> • 2 x QSFP+ (Bi-directional) 	
Control		<ul style="list-style-type: none"> • 1 x RJ45 Ethernet • USB (RS232 via dongle, IR emitter via dongle for E1000-3D) 	
Power	input rating	<ul style="list-style-type: none"> • 100-240 VAC @ 50/60Hz 	
	power consumption	<ul style="list-style-type: none"> • 30W 	
	heat output	<ul style="list-style-type: none"> • 102 BTU/hr 	
Physical	size	<ul style="list-style-type: none"> • (LxWxH): 11.2 x 8.7 x 1.7" (285.5 x 220.2 x 42.8mm) 	
	weight	<ul style="list-style-type: none"> • 1.5kg 	
Environment	operating temperature	<ul style="list-style-type: none"> • 32-104°F (0-40°C) 	
	operating humidity	<ul style="list-style-type: none"> • 10-90% RH non-condensing 	
	storage temperature	<ul style="list-style-type: none"> • 14-122°F (-10-55°C) 	
	environment	<ul style="list-style-type: none"> • Indoor 	
Warranty		<ul style="list-style-type: none"> • Three year parts and labor limited warranty, extended warranty option available for a one-time fee at time of purchase 	



◀ Christie Link E1000 / E1000-3D



^ Christie Link E1100



For the most current specification information, please visit christiedigital.com

Copyright 2020 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD1146_Christie_Link_Controller_SpecSheet_Feb-20



CHRISTIE®