

# Christie LX602

## Compact, easy-to-install, value-added 3LCD projector




Technical specifications		Christie LX602
Image	brightness (lumens)	• 6200 ISO • 5475 ANSI
	dynamic contrast	• 10,000:1
Display technology	type	• 3 x 0.63" Inorganic LCD
	native resolution	• 1024 x 768 XGA
Lamp	type	• 1 x 300W UHB
	typical lifetime	• Standard mode: up to 4000 hrs • Eco mode: up to 6000 hrs
Inputs	signals	• VGA/SVGA/XGA/WXGA/WXGA+/SXGA/SXGA+/WSXGA+/UXGA/WUXGA/MAC 16" • NTSC, NTSC4.43, PAL, PAL-M, PAL-N, SECAM 480i • 480p, 576i, 720p, 1080i, 1080p
	scan rates	• Horizontal: 32-106kHz • Vertical: 56-120Hz
	standard	• Computer Input: 15-pin D-sub x 1 • Digital Input: HDMI x 2 • Video Input: Composite video RCA jack x 1, Component video 15-pin D-sub x 1 • Audio Input: 3.5mm stereo mini jack x 1, RCA jack (L/R) x 1 • USB Type A x 1 (for wireless network)
Outputs		• HDMI x 1 • 15-pin D-sub x 1 • Audio output 3.5mm stereo mini jack x 1
Control and networking		• 9-pin D-sub x 1 (RS-232C) • RJ45 port
Accessories	standard	• IR remote • AC line cords for projector head • RGB cable • Adapter cover • Lens covers • User documentation
	optional	• Ceiling mount (108-506102-01) • 300W UHB lamp (003-005852-01) • Air filter (003-005853-01) • USB wireless adapter (121-116109-XX)
Lens	adjustment	• Zoom, focus and lens shift
	lens	• 1.4-2.3:1, 1.6x manual zoom
Power requirements	operating voltage	• 100-120 VAC @ 50/60Hz • 220-240 VAC @ 50/60Hz
	consumption	• 440W @ 100 -120 VAC • 420W @ 220-240 VAC
	operating current	• 4.4A @ 100 VAC • 2.2A @ 220 VAC
	dissipation	• 1502 BTU/hr @ 100-120 VAC • 1433 BTU/hr @ 200-240 VAC
Audible noise		• Standard mode: 39dB(A) • Eco mode: 30dB(A)
Physical	size	• (LxWxH) 13.3 x 18.3 x 5.4" (338 x 466 x 138mm) w/o feet
	shipping size	• (LxWxH) 18.8 x 22 x 9.7" (478 x 560 x 246mm)
	weight	• 15.2lbs (6.9kg)
	shipping weight	• 21.8lbs (9.9kg)
Operating environment	temperature	• 32-104°F (0-40°C)
	altitude	• 0-10,000ft (3048m)
	humidity	• 10-85% non-condensing
Key features		• Long-life lamp up to 6000 hrs (eco mode) • AMX and Crestron connectivity • Hybrid filter up to 10,000 hrs • DICOM simulation mode • HDCR • Picture-in-Picture/Picture-by-Picture • Edge blending • Warping • Zoom, focus, H/V lens shift • HDMI-Out • Closed caption • Built-in keypad • 3D Keystone • Wireless capable • 16W built-in audio
Regulatory		• Directives: RoHS • REACH • WEEE • UL/CSA/IEC 60950-1 • FCC Class A • *CCC *CEL (GB32028-2015) *CECP (CQC6102-2016)
Warranty		• Three years on the projector • Contact an authorized Christie representative for full details of our limited warranty


### Front view




### Side view



### Top view



### Back view



### Christie® support and services

All Christie products are backed by industry-leading warranties, renowned service and support. We ensure our customers are well supported with training, service and technical knowledge through our extensive distribution and support network.

United Kingdom  
Branch & EMEA  
Head Office  
ViewPoint  
200 Ashville Way  
Wokingham  
Berkshire, U.K.  
RG41 2PL  
PH: +44 (0) 118 977 8000

Middle East  
Light Industrial Unit (LIU-17)  
Nad Al Shibba  
Sheikh Mohammed Bin Zayed Road  
Dubai Silicon Oasis  
PO Box: 293762  
Dubai - U.A.E  
PH: +971 (0) 4 503 6800

Africa  
Unit C3  
Northlands Deco Park  
New Market Road  
Northriding  
Randburg  
2164  
Johannesburg  
Gauteng  
South Africa  
PH: +27 11 251 0000

### Other EMEA offices

Germany  
Branch Office  
PH: +49 2161 566 200

France  
Branch Office  
PH: +33 (0) 1 41 21 44 04

Spain  
Branch Office  
PH: +34 91 633 9990

Italy  
Independent Sales Consultant Office  
PH: +39 (0) 2 9902 1161

Russia  
Independent Sales Consultant Office  
PH: +7 (495) 930-8961



For the most current specification information, please visit [www.christieemea.com](http://www.christieemea.com)

Copyright 2018 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4617 Dec 17

**CHRISTIE®**