

Christie Velvet

E600 controller

Technical specifications

| | | |
|-------------|-----------------------|---|
| Inputs | | <ul style="list-style-type: none"> • 1 x DP (HDCP compatible) • 1 x HDMI™ (HDCP compatible) • 2 x Dual-link DVI |
| GenLock | | <ul style="list-style-type: none"> • 1 x BNC in • 1 x BNC loop |
| Outputs | | <ul style="list-style-type: none"> • 16 x Neutrik Gigabit Ethernet • 4 x Optical Fiber |
| Control | | <ul style="list-style-type: none"> • 1 x RJ45 Ethernet • 1 x USB-A link-in • 1 x USB-B link-out • 1 x USB-B (front panel) |
| Accessories | | <ul style="list-style-type: none"> • USB cable (1.5m) • HDMI cable (1.5m) • DP cable (1.5m) • Ethernet cable (1.5m) |
| Power | input rating | • 100-240 VAC @ 50/60Hz |
| | power consumption | • 30W |
| | heat output | • 102 BTU/hr |
| Physical | size | • (LxWxH) 19.0 x 14.6 x 3.5" (482.6 x 370.0 x 89.0mm) |
| | weight | • 9lbs (4.1kg) |
| Environment | operating temperature | • -4-140°F (-20-60°C) |
| | operating humidity | • 10-90% |
| | storage temperature | • -14-122°F (-26-55°C) |
| Warranty | | <ul style="list-style-type: none"> • Three years parts and labor limited warranty • Contact an authorized Christie® representative for full details of our limited warranty |

For the most current specification information, please visit christiedigital.com

Copyright 2019 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. 4633 Nov 19



CHRISTIE®