




direct-view products

LCD panels

Christie Access II Series | Corporate | Education | Retail | Digital signage

<p>Model(s)</p> <ul style="list-style-type: none"> • UHD552-L • UHD652-L • UHD752-L • UHD862-L • UHD982-P-A 		<p>Specifications</p> <ul style="list-style-type: none"> • Size range: 55-98" • Native resolution: 4K UHD 3840 x 2160 (16:9) • Brightness range: 350 - 500 nits • Backlight: Edge- and direct-lit models • LED lifespan: 50,000 hours to 50% brightness • Run-time: 16/7 - 24/7 (983-P-A is 24/7) operation • Display orientations: Landscape - 55", 65", 75", 86", Landscape and portrait - 98" • Pixel pitch range: 0.315 x 0.315mm - 0.57 x 0.57mm • Built-in speakers 	<p>We thought of everything</p> <ul style="list-style-type: none"> • Brilliant, large-format LCD displays • 4K UHD • OPS slot • USB playback • ADA-compliant • Offers the highest brightness in the affordable display category 	<p>QR code</p> 
---	---	---	--	---

Christie Secure Series II | Government | Control rooms | Corporate | Digital signage

<p>Model(s)</p> <ul style="list-style-type: none"> • SUHD553-L • SUHD653-L • SUHD753-L • SUHD863-L • SUHD983-P 		<p>Specifications</p> <ul style="list-style-type: none"> • Size range: 55"- 98" • Native resolutions: 4K UHD 3840 x 2160 (16:9) • Brightness range: 450-500 nits • Backlight: Direct-lit and edge-lit models • LED lifespan: 30,000 - 50,000 hours to 50% brightness • Run-time: All models designed for 18/7 operation; SUHD983-P designed for 24/7 operation • Display orientations: Landscape - 55", 65", 75", 86", Landscape and portrait - 98" • Pixel pitch range: 0.315 x 0.315mm - 0.57 x 0.57mm • Built-in speakers 	<p>We thought of everything</p> <ul style="list-style-type: none"> • Commercial-grade 4K UHD LCD panels specifically designed for secure-facility applications • Non-RF for increased security • TAA-compliant • ADA-compliant • Crestron Connected • Multiple connectivity options • 4K multi-source viewing capability 	<p>QR code</p> 
--	---	--	--	---

LCD video walls

Christie Extreme Series | Control rooms | Corporate | Education | Retail | Architecture and art galleries | Hospitality

Model(s)

- FHD554-XZ-H
- FHD554-XZ
- FHD554-XZ-HR
- FHD554-XZ-R



Specifications

- Size: 55"
- Bezel width of - 0.88mm (0.44 per display) to 1.7mm (combined)
- Native resolution: Full HD (1920 x 1080) (16:9)
- Brightness: 500 - 700 nits
- Backlight: Direct-lit
- LED lifespan: 60,000 hours to 50% brightness
- Run-time: 24/7 operation
- Display orientations: Landscape or portrait
- Pixel pitch: 0.63 x 0.63mm

We thought of everything

- Create near-seamless video walls with our Extreme-narrow bezel tiled LCD panels
- Featuring advanced panel matching and built-in video wall scaling
- Smart Light Control for uniformity and consistency
- Fast motion compensation to reduce tearing of video wall content
- 24/7 operation
- Remote and redundant power options
- ADA-compliant
- Select models are TAA-compliant

QR code



Christie Ultra Series | Critical viewing | Control rooms | Government | Corporate | Retail | Hospitality

Model(s)

- FHD554-X



Specifications

- Size range: 55"
- Bezel width range: 3.5mm
- Native resolutions: Full HD (1920 x 1080)
- Brightness range: 500
- Backlight: Direct-lit
- LED lifespan: 50,000 hours to 50% brightness
- Run-time: 24/7 operation
- Display orientations: Landscape or portrait
- Pixel pitch range: 0.63 x 0.63mm

We thought of everything

- Professional-grade, ultra-narrow bezel width for near-seamless LCD video walls
- Up to full HD, built-in video processing, and 24/7 operation
- Advanced panel matching ensures image uniformity and fast installation
- Built-in video wall scaling supports 4K signals across video walls up to 10x10 configurations
- ADA-compliant
- FHD554-X model is non-RF and TAA-compliant

QR code



LED video walls

Christie Core Series II | Public spaces | Corporate | Education | Government | Control rooms

Model(s)

- LED009-C2-I
- LED012-C2-I
- LED015-C2-I
- LED018-C2-I
- LED025-C2-I



Specifications

- Pixel pitch range: 0.9 - 2.5mm
- Brightness: 800 nits (cd/sq m)
- Pixel configuration: 3-in-1 (1R1G1B)
- Pixel density range: 1,137,777 - 160,000 pixels/sq m
- Aspect ratio: 16:9
- Contrast ratio: 5,000-1 @ 1Lux, 2,000:1 @ 10Lux
- Compatible with our E510 or E600 controller

We thought of everything

- Reliable, affordable, high-value LED video walls
- 24/7 operation
- Simple, concealed cable design
- Redundant on-board power
- Full-front access for easy installation and service
- ADA-compliant direct-mount system
- Scales to common resolutions including HD and 4K
- Powered by our E510 or E600 controller for simple system design and enhanced processing that can deliver 4K@60Hz, HDR10, and low-brightness enhancements

QR code



LED video walls (continued)

Christie MicroTiles® LED | Architectural | Broadcast | Corporate | Education | Live events | Museums | Retail | Stadiums

Model(s)

- LED 1.25 P3
- LED 1.25 NTSC
- LED 1.5 NTSC



Specifications

- Pixel pitch range: 1.25 - 1.5mm
- Brightness: 1,000 nits (cd/sq m)
- Contrast ratio: >5,000-1
- Refresh rate: Up to 3840Hz
- LED lifespan: 100,000 hours
- Run time: 24/7
- Size: 14.22" (361mm) diagonal
- Weight: 4.85lbs (2.2kg)
- Orientation – portrait (8:9) and landscape (16:9)

We thought of everything

- Advanced, cabinet-free, ultra-lightweight LED video wall technology
- Click-n-Go™ magnetic tiles eliminate alignment requirements and drastically increase installation speed
- Limitless design freedom—including 90° inside/outside corners and concave and convex curves
- Superior visual quality – Powerful processing along with HDR10 compatibility plus high-brightness and cinema-quality color for brilliant, true-to-life detail
- QuickMount™ system uses mounting sheets that help eliminate alignment challenges, and save time and money
- IR Neighbor Detection™ - Individual tiles automatically detect and self-locate
- AutoMatch™ automatically matches color and brightness for >97% uniformity across the entire display
- Christie MicroTiles LED WebUI lets you control and manage the device with our easy-to-use web-based control interface
- Experience a robust, flicker-free and uncompromised Active 3D experience at 60Hz per eye with MicroTiles LED Active 3D (optional with 1.25mm model)
- TAA-compliant

QR code



For the most current specification information, please visit christiedigital.com

Copyright 2022 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD2585_Direct-View_Line card_Mar-22



CHRISTIE®