


## Direct-view products

### LCD digital signage

#### Christie Access II Series | Corporate | Education | Retail | Digital signage

<p><b>Model(s)</b></p> <ul style="list-style-type: none"> <li>• UHD552-L</li> <li>• UHD652-L</li> <li>• UHD752-L</li> <li>• UHD862-L</li> <li>• UHD982-P-A</li> </ul>		<p><b>Specifications</b></p> <ul style="list-style-type: none"> <li>• Available sizes: 55", 65", 75", 86", 98"</li> <li>• Native resolution: 4K UHD (3840 x 2160) (16:9)</li> <li>• Brightness range: 350-500 nits</li> <li>• Backlight: Direct-lit and edge-lit models</li> <li>• LED lifespan: 50,000 hours to 50% brightness</li> <li>• Run-time: 16/7 - 24/7 (983-P-A is 24/7) operation</li> <li>• Display orientations: Landscape - 55", 65", 75", 86", Landscape and portrait - 98"</li> <li>• Pixel pitch range: 0.315 x 0.315mm - 0.57 x 0.57mm</li> <li>• Built-in speakers</li> </ul>	<p><b>We thought of everything</b></p> <ul style="list-style-type: none"> <li>• Brilliant, large-format LCD displays</li> <li>• 4K UHD</li> <li>• OPS slot</li> <li>• ADA-compliant</li> <li>• Offers the highest brightness in the affordable display category</li> </ul>	<p><b>QR code</b></p> 
---	---	--	--	---

#### Christie Secure Series II | Government | Control rooms | Corporate | Digital signage

<p><b>Model(s)</b></p> <ul style="list-style-type: none"> <li>• SUHD553-L</li> <li>• SUHD653-L</li> <li>• SUHD753-L</li> <li>• SUHD863-L</li> <li>• SUHD983-P-A</li> </ul>		<p><b>Specifications</b></p> <ul style="list-style-type: none"> <li>• Available sizes: 55", 65", 75", 86", 98"</li> <li>• Native resolution: 4K UHD (3840 x 2160) (16:9)</li> <li>• Brightness range: 450-500 nits</li> <li>• Backlight: Direct-lit and edge-lit models</li> <li>• LED lifespan: 30,000 - 50,000 hours to 50% brightness</li> <li>• Run-time: All models designed for 18/7 operation; SUHD983-P designed for 24/7 operation</li> <li>• Display orientations: Landscape - 55", 65", 75", 86", Landscape and portrait - 98"</li> <li>• Pixel pitch range: 0.315 x 0.315mm - 0.57 x 0.57mm</li> <li>• Built-in speakers</li> </ul>	<p><b>We thought of everything</b></p> <ul style="list-style-type: none"> <li>• Commercial-grade 4K UHD LCD panels specifically designed for secure-facility applications</li> <li>• Non-RF for increased security</li> <li>• TAA-compliant</li> <li>• ADA-compliant</li> <li>• Multiple connectivity options</li> <li>• 4K multi-source viewing capability</li> </ul>	<p><b>QR code</b></p> 
--	---	---	--	---

## LCD video walls

**Christie Ultra Series** | Critical viewing | Control rooms | Government | Corporate | Retail | Hospitality

### Model(s)

- FHD554-X



### Specifications

- Size: 55"
- Bezel width: 3.5mm combined
- Native resolutions: Full HD (1920 x 1080) and 4K UHD (3840 x 2160)
- Brightness range: 500 nits
- Backlight: Direct-lit
- LED lifespan: 50,000 hours to 50% brightness
- Run-time: 24/7 operation
- Display orientations: Landscape or portrait
- Pixel pitch: 0.63 x 0.63mm

### We thought of everything

- Professional-grade, ultra-narrow bezel width for near-seamless LCD video walls
- Up to 4K UHD, built-in video processing, and 24/7 operation
- Advanced panel matching ensures image uniformity and fast installation
- Built-in video wall scaling supports 4K signals across video walls up to 10x10 configurations
- ADA-compliant
- Non-RF and TAA-compliant

### QR code



## LED video walls

**Christie Core Series III** | Public spaces | Corporate | Education | Government | Control rooms

### Model(s)

- LED009-C3-I
- LED012-C3-I
- LED015-C3-I
- LED018-C3-I
- LED025-C3-I



### Specifications

- Pixel pitches: 0.9mm, 1.2mm, 1.5mm, 1.8mm, 2.5mm
- Brightness: 800 nits (cd/m<sup>2</sup>)
- Pixel density range: 1,137,777 - 160,000 pixels/m<sup>2</sup>
- Aspect ratio: 16:9
- Contrast ratio: 5,000-1 @ 1Lux, 2,000:1 @ 10Lux
- Compatible with our E600 controller

### We thought of everything

- Reliable, affordable, high-value LED video walls
- Lighter and more power efficient than previous models
- Simple, concealed cable design
- Redundant on-board power
- Full-front access for easy installation and service
- ADA-compliant direct-mount system
- Scales to common resolutions including HD and 4K
- Powered by our E600 controller for simple system design and enhanced processing that can deliver 4K at 60 Hz, HDR10, and low-brightness enhancements

### QR code



## LED video walls (continued)

Christie MicroTiles LED | Architectural | Broadcast | Corporate | Museums | Government | Control rooms

### Model(s)

- LED 0.75mm P3
- LED 1.0mm P3
- LED 1.25mm P3
- LED 1.25mm NTSC
- LED 1.5mm P3
- LED 1.5mm NTSC



### Specifications

- Pixel pitches: 0.75mm, 1.0mm, 1.25mm, 1.5mm
- Brightness: 1000-2000 nits (cd/m<sup>2</sup>)
- Contrast ratio: >5,000-1 up to >10,000-1
- Refresh rate: Up to 3840 Hz
- Run time: 24/7
- Installation options: Flat, Concave, Convex, 90 degree outside and inside corner, Hanging/flying, and other Creative shapes
- Color space: P3 and NTSC
- Display colors: 281 trillion (16-bit) to 18 quadrillion (16-bit)

### We thought of everything

- Advanced, cabinet-free, ultra-lightweight MicroTiles® LED video wall technology
- Click-n-Go™ magnetic tiles eases alignment and increases installation speed
- Powerful processing along with HDR10 compatibility and cinema-quality color for brilliant, true-to-life details
- IR Neighbor Detection™ - Individual tiles automatically detect and self-locate
- AutoMatch™ automatically matches color and brightness for >97% uniformity across the entire display
- Increased reliability - The 0.75 and 1.0mm models are more reliable, easier to maintain
- Increased durability - The surface of the 0.75 and 1.00mm models helps protect against dust and scratches
- TAA-compliant

### QR code



**CHRISTIE**<sup>®</sup>

[christiedigital.com](http://christiedigital.com)

For the most current specification information, please visit [christiedigital.com](http://christiedigital.com)

Copyright 2024 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP<sup>®</sup> and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.  
CD4802-Direct-view-line-cards-update-Jul-24-EN

