

Christie MicroTiles LED

Indoor LED tiles



Technical specification

0.9mm

Display technology	pixel pitch	• 0.9375mm
	pixel configuration	• 4 pixels in 1 package (4R4G4B)
	maximum calibrated brightness	• 1500 nits (cd/m ²) calibrated
	aspect ratio	• 1:1
	contrast ratio (full field)	• Greater than 5000:1
	viewing angle	• 160° H, 160° V
	LED refresh rate	• 3840 Hz
	input refresh rate	• 120 Hz
	scan rate	• 1/48
	color temperature	• 2700-9600K
	display colors	• 18014 trillion (18-bit)
	color space	• DCI-P3
	LED lifespan (50% brightness)	• 100,000 hours
	runtime	• 24/7
Signal	inputs	• 2 x HDMI 2.0 (HDCP), 2 x DisplayPort 1.2 (HDCP)
	outputs	• 2 x QSFP+ (Bi-directional)
	control	• 1 x RJ45 Ethernet, USB (RS232 via dongle)
Power	power input rating	• 100-240 VAC @ 50/60 Hz - remote power supply ¹ • 48-56 VDC • 48V Power over Ethernet - per tile
	power consumption per tile	• 15 W typical, 35 W maximum
	heat output per tile	• 51 BTU/hr typical; 119 BTU/hr maximum
Environment	operating temperature	• 32-104F (0-40C)
	operating humidity	• 10-90% RH non-condensing
	storage temperature	• 14-122F (-10-50C)
	environment	• Indoor
	IP rating	• 30
Physical	tile dimensions (installed)	• (W x H x D) 10.63 x 10.63 x 3.35" (270 x 270 x 85mm)
	tile diagonal	• 15.40" (391.2mm)
	tile area	• 0.7857ft ² (0.0729m ²)
	tile resolution	• 288 x 288
	tile weight	• 78.03lbs (35.39kg) per square meter
	tile design	• Die-cast aluminum
	service access	• All service from front
	installation options	• Flat • Concave • Convex • Hanging/flying • Creative shapes
	direct mount system	• QuickMount system included - mounting plates, mounting template, wall anchors
	additional required components	• Remote power supply rack shelf • Power supply unit modules (rectifiers) • Tile controller (Octroller), and wall controller sold separately
	additional features	• TAA-compliant.
	Certifications ²	• UL60950, FCC, CE, RoHS
Warranty	• Three years parts and labor limited warranty, extended warranty option available for a one-time fee at time of purchase	

¹ See remote power specifications for full details.

² Certain of the listed certifications may be pending and not yet issued. For the current status of the listed certifications, please contact an authorized Christie representative.


Performance specifications are typical. Due to constant research, specifications are subject to change without notice.

Octroller

Signal	
inputs	• 2 x QSFP+ (Bi-directional)
outputs	• 8 X RJ45 Ethernet (PoE up to 75W per port)
Power	
power input rating	• 48-56 VDC
power consumption	• 25W maximum
Environment	
operating temperature	• 32-104F (0-40C)
operating humidity	• 10-90% RH non-condensing
storage temperature	• 14-122F (-10-50C)
environment	• Indoor

QuickMount system

Proprietary QuickMount system includes custom mounting templates, laser-cut steel mounting sheets and machined wall anchors to eliminate any alignment challenges, reducing time and cost.



For the most current specification information, please visit christiedigital.com

Copyright 2026 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.
CD70101CD4615-MicroTilesLED-0.9mm-data-sheet-Jan-26-EN

CHRISTIE®